## **EUROPOWER SERIES** Line Interactive 1000VA UPS



Europower series Line Interactive UPS is integrated with AC voltage stabilizer, surge voltage suppression, with its compact size, full function, high efficiency, high reliability, easy to use suitable for office spaces and homes. Line interactive UPS is always in by-pass mode while the mains is on and during power outage it provides electricity for the connected device. They are commonly used for computers in home or offices. Operating time of the line interactive UPS cannot be increased by adding extra batteries. For long-time operations an online UPS must be used.



## **General Features**

- Compact Size
- Microprocessor Control
- Boost and Buck AVR for Voltage Stabilization
- Auto Restart While AC is Recovering
- Sine Wave Output
- Off-mode Charging
- Cold Start Function
- Generator Compatible
- Optional RS232/USB Interface for Communication
- Modem/LAN Internet Protection
- Built-in Self-Diagnostics
- Best for PC, Tablets, Office Equipment
- High Reliability and Lifetime

SPECIFICATIONS
----------------

MODEL		CNE-1000LU
Capacity	VA	1000 VA
Input	Voltage	220/230/240 Vac
	Voltage Range	162-290 Vac
	Frequency Range	60/50 Hz (auto sensing)
Output	Voltage	220/230/240 Vac
	AC Voltage Regulation (Batt. Mode)	±10%
	Frequency Range (Batt. Mode)	60 Hz or 50 Hz +/-10%
	Transfer Time	<4 ms
	Waveform (Batt. Mode)	Sinewave
Battery	Battery Type & Number	1000 VA
	Typical Recharge Time	4 hours recover to 90% capacity
Indicators	AC Mode	Green lighting
	Battery Mode	Yellow flashing
	Fault	Red lighting
Alarm	Battery Mode	Beeps every 10 seconds
	Low Battery	Beeps every second
	Overload	Beeps every 0.5 second
	Fault	Continuously beeping
Protection	Full Protection	Overload, discharge, and overcharge protection
Environment	Humidity	0-90 % RH @ 0- 40°C (non-condensing)
	Noise Level	Less than 40dB
Outlets	Outlets	4 no x C13 Outlet
Physical	Dimension	320 x 130 x 182
	Weight	8.2

## **ORDERING INFORMATION**

Part Number	Description
CNE-1000LU	1000VA Line Interactive UPS