

PLINTH



Material	SPCC cold rolled steel
Thickness	Plate: 1.2 mm, Others: 2.0 mm
Surface Finish	Degreasing, phosphoric, powder coated
Loading Capacity	20 Kg
Flexing length	220 mm

ORDERING INFORMATION

Part Number	Description	Dimension (mm)		
		W	D	H
1333-66X	Plinth 600 Width and 600 Depth	596	596	100
1333-68X	Plinth 600 Width and 800 Depth	596	796	100
1333-61X	Plinth 600 Width and 1000-Depth	596	996	100
1333-88X	Plinth 800 Width and 800 Depth	796	796	100
1333-81X	Plinth 800 Width and 1000 Depth	796	996	100
1333-8BX	Plinth 800 Width and 1200 Depth	796	1196	100

X: R1(RAL 9004), R2(RAL 7035), R3(RAL 9010)

PACKING INFORMATION

Part Number	Packing Qty.	Packing Mode	N.W (kg)	G.W (kg)	Dimension (mm)
1333-66X	1 x 1	Carton Box	3.9	4.5	620 x 620 x 600
1333-68X	1 x 1	Carton Box	5.3	6.0	620 x 820 x 600
1333-61X	1 x 1	Carton Box	6.5	7.0	620 x 1020 x 600
1333-88X	1 x 1	Carton Box	6.5	7.0	820 x 820 x 600
1333-81X	1 x 1	Carton Box	8.7	9.5	820 x 1020 x 600
1333-8BX	1 x 1	Carton Box	10.5	11.5	820 x 1220 x 600