

# IP 65 AIR CONDITIONED FLOOR STANDING CABINET



The Easycab range of floor standing cabinet IP65 with 600W Air Condition is designed for external telecommunication purpose. The smart design and professional engineering provides easy installation and maintenance. It is comply with GB/T 19183 and IEC 61969.

## FEATURES

- Double wall type design with 500W / 600W / 1000W / 1500W Air Condition.
- Bolts are fixed inside, no trace design
- Rain awnings on top
- Bottom wire path, cover with rubber
- Front door with handle lock, extra space for AC if needed
- With 20cm height plinth / IP65 without fans With earthing /with 1 fixed shelf
- The cabinet comes with 2 entrance guards, 1 smoke sensor and 1 temperature sensor.
- A filter screen and rubber strip are installed within the cabinet to keep out dust and water.

Material	Galvanized sheet
Deg. of Protection	IP 65
Surface finish	Degrease, acid pickling, rust prevention and parkerizing, pure water cleaning, static electricity plastic painting
Loading capacity	800 Kg
Material thickness	Mounting Rails: 2.0mm, Others: 1.5-2.0mm
Operation Temperature	-40°C to +55°C
Relative Humidity	Less than or equal to 95 percent (+35°C)
Atmospheric Pressure	70KPa to 106Kpa

## ACCESSORIES

No.	Item	800wide	Materials	Treatment	Note
1.	Frame	2	2.0mm galvanized steel	Powder coating	
2.	Front Door	1	1.5mm galvanized steel	Powder coating	with file box
3.	Side Door	2	1.5mm galvanized steel	Powder coating	Unremovable
4.	Back Door	1	1.5mm galvanized steel	Powder coating	
5.	Lock	1	\	\	Handle Lock
6.	Top cover	1	1.5mm galvanized steel	Powder coating	With water proof panel
7.	Door seal	1	Black Rubber	\	
8.	Door knob	1	galvanized steel T=1.5	GE	
9.	Release fastener	6 or 12	galvanized steel=1.5	Powder coating	H≤27U, 6pcs
10.	Bottom panel	1	galvanized steel=1.5	Powder coating	
11.	Mounting angle	6	galvanized steel=1.5	Powder coating	H≤27U, 4pcs
12.	Mounting profile	4	galvanized steel=2.0	Zinc plated	
13.	Plinth	1	galvanized steel=2.0	Powder coating	L=10 to 20 cm

# IP 65 AIR CONDITIONED FLOOR STANDING CABINET



## ORDERING INFORMATION

Part Number	Description	Capacity (U)	Dimension (mm)
132T-186622X	18U 600x600 IP 65 Front & Back Metal Door Floor Standing Cabinet with 600W air condition	18	600 X 600 X 1000
132T-228822X	22U 800x800 IP 65 Front & Back Metal Door Floor Standing Cabinet with 600W air condition	22	800 X 800 X 1300
132T-228822X - 4	22U 800 x 800 IP 65 Front & Back Metal Door Floor Standing Cabinet with 1500W Air Condition	22	800 x 800 x 1300
132T-238622X	23U 800 X 600 IP 65 Front & Back Metal Door Floor Standing Cabinet with 600W Air Condition	23	800 X 600 X 1200
132T-278822X	27U 800x800 IP 65 Front & Back Metal Door Floor Standing Cabinet with 600W air condition	27	800 X 800 X 1550
132T-278822X - 4	27U 800 x 800 IP 65 Front & Back Metal Door Floor Standing Cabinet with 1500W Air Condition	27	800 x 800 x 1550
132T-428122X	42U 800 X 1000 IP 65 Front & Back Metal Door Floor Standing Cabinet with 1000W air Condition	42	800 X 1000 X 2055

X: R1(RAL 9004), R2(RAL 7035), R3(RAL 9010)

## PACKING INFORMATION

Part Number	Packing Qty.	Packing Mode	N.W (kg)	G.W (kg)	Dimension (mm)
132T-186622X	1 x 1	Carton + Wooden Pallet	85.0	90.0	600 X 600 X 1025
132T-228822X	1 x 1	Carton + Wooden Pallet	110.0	120.0	800 x 800 x 1320
132T-228822X - 4	1 x 1	Carton + Wooden Pallet	110.0	120.0	800 x 800 x 1320
132T-238622X	1 x 1	Carton + Wooden Pallet	140.0	155.0	800 X 820 X 1350
132T-278822X	1 x 1	Carton + Wooden Pallet	120.0	130.0	800 x 800 x 1570
132T-278822X - 4	1 x 1	Carton + Wooden Pallet	120.0	130.0	800 x 800 x 1570
132T-428122X	1 x 1	Carton + Wooden Pallet	220.0	240.0	800 X 1000 X 2070