

# 32CH NETWORK VIDEO RECORDER



## ENR-04032-N-SPK

### FEATURES

32 Channel input
Support H.265+, H.265, H.264 video formats
4 SATA HDDs
Support RAID (0/1/5/6/10)
eSATA Interface
ONVIF Profile S
PoE Support



### SPECIFICATION

MODEL	Model No.	ENR-04032-N-SPK
	Type	32CH NETWORK VIDEO RECORDER
VIDEO & AUDIO	Video Input	32-Ch
	Incoming Bandwidth	320Mbps
	Outgoing Bandwidth	320Mbps
	HDMI/VGA Output	HDMI 1: 3840x2160, 1920x1080, 1280x1024, 1024x768 HDMI 2 / VGA: 1920x1080, 1280x1024, 1024x768
	Audio Input / Output	1-ch Input/ 1-ch Output
	Two way Audio	Supported
	Multi-screen Display	1st Screen: 1/4/8/9/16/32 2nd Screen: 1/4/8/9/16
	OSD Type	Channel Name, Date
DECODING	Video Compression	H.265+, H.265, H.264
	Audio Compression	G.711A/G.711U
	Bit Rate Type	CBR, VBR
	Recording Resolution	12MP, 8MP, 6MP, 5MP, 4MP, 3MP, 1080P, 720P, D1
	Recording Mode	Manual, Schedule (Regular, Continuous), Event
	Trigger Events	Motion Detection, Video Loss, Alarm in, IVS
	Decoding Capability	1x12MP, 4x4MP, 9x1080P, 16xD1, 32xD1
MONITORING	Synchronous Playback	16/9/4/1
	Live View Functions	Snapshot, Record, Digital Zoom, Record, PTZ Toolbar, Volume Adjustment, Image Setting
	Playback functions	Sync Playback, Play, Pause, Stop, Fast play, Slow Play, Full Screen, Backup Selection, Snapshot, Search by Date, Picture Grid
	Search Mode	Time/Date, Alarm, Picture grid, Event
	Backup Mode	USB, Network, eSATA
	Export Picture Format	MP4

★Product specification and availability are subject to change without notice.



# 32CH NETWORK VIDEO RECORDER



## ENR-04032-N-SPK

MODEL	Model No.	ENR-04032-N-SPK
	Type	32CH NETWORK VIDEO RECORDER
INTERFACE	Protocols	TCP/IP, UDP, IPv4, IPv6, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP/RTSP/RTCP, PPPoE, NTP, UPnP, QoS, SMTP, IGMP, 802.1X, NFS, Unicast, Multicast, ARP, SNMP, SSL, Telnet, SFTP (SSH), P2P, 3G/4G
	Compatibility	ONVIF Profile S, SDK / CGI
	Network	2xRJ45 (10/100/1000 Mbps) Self Adaptive Ethernet Port
	Serial Interface	1xRS485, 1xRS232
	USB Interface	2xUSB 2.0, 1xUSB 3.0
	Alarm Interface	6 Input & 2 Output
PoE	PoE Interface	16 RJ-45 (10M/100M) Self Adaptive Ethernet Port
	Power for PoE Port	140W
SMART	Alarm Management	Input & Output Event, Alarm I/O Error, IP Conflict, Hard Disk Full, No Hard Disk, Hard Disk R/W Error, HDD SMART Check Error, Abnormal Recording, Hot Spare Error & Array Error, Motion Detection, Tampering (Masking), Smart detection, Video loss
	Behavior Detection	Intrusion (Perimeter), Crossline (Tripwire), Double Crossline (Double Tripwire)
	Analytics	Loitering, Multi Loitering, Abandoned object (Object Left), Missing object (Object Lost), People Counting, Wrong Way Detection, Abnormal Speed, Illegal Parking *Compatible with analytic supported cameras
STORAGE	SATA	4 SATA Interfaces
	Capacity	Up to 16TB for each HDD
	Array Type	RAID 0/1/5/6/10
	eSATA	Supported
	ANR	Supported
GENERAL	Operating System	Embedded Linux
	Remote Users	8
	Client Application	EyeGuard
	Power	100 ~ 240V AC
	Redundant Power	N/A
	Power Consumption (without HDD)	≤15W
	Working Environment	-10°C ~ 55°C
	Working Humidity	<90% RH
	Chassis	1.5U
	Dimension	440 × 368.3 × 70 mm
Net Weight (without HDD)	4.65 kg	

Dimension Unit : mm



### ORDERING INFORMATION

Part Number	Description	Standard Quantity
ENR-04032-N-SPK	32Ch Embedded Network Video Recorder with 4 HDD Bays Supports 16# PoE Ports, 4K Cameras, RAID, HDMI, VGA and ONVIF	1

### PACKING INFORMATION

Part Number	Packing Mode	Gross weight(Kg)	Dimension(mm)
ENR-04032-N-SPK	Carton Box	-	-

★Product specification and availability are subject to change without notice.