


# 32CH EMBEDDED NETWORK VIDEO RECORDER



**ENR-02032-N-FK**

## FEATURES

- 32 Channel Input
- Support H.265+, H.265, H.264 Video Formats
- HDMI and VGA Interfaces
- 2 SATA HDDs
- ONVIF Profile S



## SPECIFICATION

MODEL	Model No.	ENR-02032-N-FK
	Type	32CH EMBEDDED NETWORK VIDEO RECORDER
VIDEO & AUDIO	Video Input	32-Ch
	Incoming Bandwidth	160 Mbps
	Outgoing Bandwidth	80 Mbps
	HDMI / VGA Output	HDMI 1: 3840×2160, 1920×1080, 1280×1024, 1024×768 VGA: 1920×1080, 1280×1024, 1024×768
	Audio Input / Output	1/ 1
	Two-way Audio	Supported
	Multi-screen Display	1/4/9/16/32
	Video Encryption	Supported
	OSD	Channel Name, Date
DECODING	Video Compression	H.265+, H.265, H.264
	Audio Compression	G.711A/G.711U
	Bit Rate Type	CBR,VBR
	Recording Resolution	12MP/8MP/6MP/5MP/4MP/3MP/1080P/720P/D1
	Recording Mode	Continuous, Manual, Event(Pre/Post, Motion etc.), Schedule
	Trigger Events	Motion Detection, Video Loss, Alarm in, IVS
	Decoding Capability	1x12MP, 1x8MP, 4x4MP, 8x1080P, 32xD1, 16xD1
MONITORING	Synchronous Playback	16/9/4/1
	Live View Functions	Snapshot, Record, Digital Zoom, Record, PTZ toolbar, Volume adjustment, Image Setting
	Playback functions	Sync playback, Play, Pause, Stop, Fast play, Slow play, Full Screen, Backup selection, Snapshot, Search by date, Picture grid
	Search Mode	Time/Date, Alarm, Picture grid, Event
	Backup Mode	USB, Network
	Export Video Format	MP4

★Product specification and availability are subject to change without notice.

# 32CH EMBEDDED NETWORK VIDEO RECORDER



**ENR-02032-N-FK**

<b>MODEL</b>	Model No.	<b>ENR-02032-N-FK</b>
	Type	32CH EMBEDDED NETWORK VIDEO RECORDER
<b>INTERFACE</b>	Protocols	TCP/IP, UDP, IPv4, IPv6, HTTP, HTTPS, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, NFS, FTP, UPnP, SMTP, SNMP, P2P, IP Filter, 802.1X, 3G/4G
	Compatibility	ONVIF Profile S, SDK/CGI
	Network	2xRJ45 (10/100/1000 Mbps) Self Adaptive Ethernet Port
	USB Interface	2xUSB 2.0
	Alarm Interface	8 Input / 1 Output
<b>HDD</b>	SATA	2 SATA interfaces
	Capacity	Up to 8 TB for each HDD
	ANR	Supported
<b>SMART</b>	Alarm Management	Input & Output event, Alarm I/O error, IP Conflict, Hard disk full, No hard disk, Hard disk RW error, HDD SMART check error, Abnormal recording, Motion detection, Tampering (Masking), Smart detection, Video loss
	Behavior Detection	Intrusion (Perimeter), Crossline (Tripwire), Double Crossline (Double Tripwire)
	Analytics	Loitering, Multi Loitering, Abandoned object (Object Left), Missing object (Object Lost), People Counting, Wrong Way Detection, Abnormal Speed, Illegal Parking *Compatible with analytic supported cameras
<b>GENERAL</b>	Operating System	Embedded Linux
	Remote Users	8
	Client Application	Eye Guard
	Power	DC 12V / 3A
	Redundant Power	N/A
	Power Consumption (without HDD)	≤15 W
	Working Environment	-10 °C ~ 55 °C
	Humidity	< 90% RH
	Chassis	1U
	Dimension	372x310.5x46.5 mm
Net Weight	1.8 kg	

Dimension Unit : mm



## ORDERING INFORMATION

Part Number	Description	Standard Quantity
ENR-02032-N-FK	32Ch Embedded Network Video Recorder with 2 HDD Bays Supports 4K Cameras, HDMI, VGA and ONVIF	1

## PACKING INFORMATION

Part Number	Packing Mode	Gross weight(Kg)	Dimension(mm)
ENR-02032-N-FK	Carton Box	-	-

★Product specification and availability are subject to change without notice.