

# CAT6 UNSHIELDED PUNCH DOWN KEYSTONE JACK



## PRODUCT OVERVIEW

Accell Unshielded punch down keystone jack exceed TIA/EIA and ISO component and channel performance, can be used in unloaded patch panels and face plates, in a variety of colour options. These Jacks are designed to reduce the Insertion loss & Alien cross talk in order to provide maximum flexibility and high performance and are available in a 180° orientation with a dual termination block which will allow the installer to terminate with either a 110 or Krone insertion tool. This supports T568 A & B wiring & easy installation. The jack is manufactured with an integral cable strain relief.

## COMPLIANCE

IEEE 802.af, IEEE 802.3at for PoE applications.  
ANSI/TIA-568-C.2, ISO/IEC-11801, EN50173-2

## DESIGN & MATERIALS

Colour	Black or Others Available Upon Request
Size	26.2x17x35.1 mm
Angle	180 Degree
Temperature	-40 °C to +70 °C (Storage), -10 °C to +65 °C (Operation)
Housing Material	High Impact, Flame-Retardant Plastic Compound, UL 94 V-0
IDC Type	Dual (110 Or Krone) Type
IDC Wire Gauge	22-26 AWG, Solid or Stranded
Colour Coding	As Per 568 A/B Standard

## STANDARDS

Flammability Rating	UL 94 V-0
Safety Rating	UL 1863

## ELECTRICAL DATA

Current Rating	1.5 A
Insulation Resistance	500 MΩ min 100 V dc
Voltage Rating	230 V rms max.
Dielectric Voltage	1000 V DC or AC, 60 Hz for 1 min (Contact-Contact)

# CAT6 UNSHIELDED PUNCH DOWN KEYSTONE JACK

---

## ORDERING INFORMATION

Part Number	Description
AKJ211180X	Cat 6 Unshielded Keystone Jack Punch Down 180D

## PACKING INFORMATION

Part Number	Packing Qty.	Packing Mode	N.W (kg)	G.W (kg)	Dimension (mm)
AKJ211180X	96 x 20 x 1	Carton Box	16.0	20.0	620 x 420 x 430