

PA SYSTEM REMOTE PAGING MICROPHONE



Descriptions

NVS-PA0015006PM is a type of multifunctional microphone. Each microphone is able to control six partitions. It is also possible to control any partition separately or to switch on and off any partition on the one-key basis, showing a high extent of humanization. The multistage expansion is supported.

FEATURES

- ⦿ Level indication;
- ⦿ Up to six partitions under control;
- ⦿ Two built-in bell signals;
- ⦿ Adjustable volume of microphone and bell;
- ⦿ Gooseneck microphone in specification of NVS-PA0015006PM;
- ⦿ RJ45 socket is used for connection between microphones, and cascading connection is supported

Specifications	
Model	NVS-PA0015006PM
Mic input sensitivity	10±2mV (unbalanced input)
Line input sensitivity	2±0.1V (balanced input)
Signal output	2±0.1V (balanced output)
Frequency response	Mic: 100Hz~15kHz (±3dB); Line: 20Hz~20kHz (±3dB)
Signal to noise ratio	Mic input ≥60dB Line output ≥70dB
Dimension of equipment (L×W×H mm)	232×146×68mm
Packing size (L×W×H mm)	282×200×264mm
Net weight	1.9kg
Gross weight	2.6kg

NVS-PA0015006PM

PA SYSTEM REMOTE PAGING MICROPHONE

ORDERING INFORMATION

Part Number	Description	Standard Quantity
NVS-PA0015006PM	PA System Remote Paging Microphone	1 No.

PACKING INFORMATION

Part Number	Packing Mode	Gross Weight(kg)	Dimensions(mm)
NVS-PA0015006PM	Carton Box	2.6	282×200×264