

20W Coaxial Ceiling Speaker with multiple Power Tap option



DESCRIPTION

The NVS-10380020CS is a Ceiling Speaker with built-in 70V/100V transformer and it can be switched between voltage terminal and the ohms terminal. The transmission takes place in a high-voltage, low-current environment. Low-current mode allows for longer transmission distances and parallel connections of many loudspeakers. The built-in 5" speaker driver has a wide frequency response (60-20,000Hz) and a 20W rated power output. It is made of high-quality engineering plastic, which assure a long-term durability and never out of shape and it will not color fade. It is an ideal choice for industrial and commercial applications like hotel, school, office and factory where background music and paging is required.

FEATURES

- ⦿ Clear and sonorous sound
- ⦿ Rated power output at 20W
- ⦿ In-ceiling type loudspeaker
- ⦿ Secure flush mount installation
- ⦿ Driver surround excellent damping
- ⦿ Equipped with voltage and ohms terminal
- ⦿ ABS white engineering plastic
- ⦿ Built-in 100V/70V transformer

Specifications	
Model	NVS-10380020CS
Rated Power	20W
Driver Size	5" x 1, 1" x1
Power Taping Options	5/10/20W
Input Voltage/Impedance	70/100V, 4-16Ω
Frequency Response	60Hz-20kHz
Sensitivity(1m,1w)	90dB
Maximum SPL(1m)	103dB
Weight	2.9kg
Dimension	Ø196 x 223 mm
Cutout Size	Ø170mm

ORDERING INFORMATION

Part Number	Description	Standard Quantity
NVS-10380020CS	20W Coaxial Ceiling Speaker with multiple Power Tap option	1