

IEC C13/C19 PDU WITH MAIN SWITCH



NORDEN Power Distribution Units are designed and manufactured in a modularized way exclusively for cabinets. The product is equipped with supply socket modules meeting different systems and standards in the world. The series products can be produced accordingly to customer's special requirement, the longest dimension can reach to 4600 mm, and load can reach to double 32A. No change to the cabinet or additional parts is necessary for product installation.

COMPLIANCE

EMC & safety:-EN 55022 Class A,EN 55024,EN 61000-3-2,EN 61000-3-3,FCC Part 15 Class A, ICES-003,PSE, VCCI Class A,VDE
Environmental: RoHS, REACH: Contains No SVHCs
Socket/Outlet Standard: IEC C13/C19

DESIGN & MATERIALS

Material of Construction	PC/ABS alloy, High Impact flame retardant thermoplastic –UL94-V0
Shell Material & Colour	Aluminium, black
Outlet Qty.	Customizable
Power Input Style	Left end single input style
Bracket Installation Style	Frontal Installation Style
Control function	Switch
Lead length	1.8m (other cable length available on request)

ELECTRICAL & ENVIRONMENTAL DATA

Phase	Single Phase / Three Phase
Current Rating	16A, 32A
Maximum load current	16A, 32A
Input frequency	50 or 60 Hz
Maximum load capacity	4KW
Operating Environment	-5°C to +45°C
Operating Relative Humidity	5 – 95 %
Operating Elevation	0-3000 meters
Storage Temperature	-25°C to +65°C
Storage Relative Humidity	5 – 95 %
Storage Elevation	0-15000 meters

IEC C13/C19 PDU WITH MAIN SWITCH

ORDERING INFORMATION

Part Number	Description
1522-406B06N001X	6 Way PDU with IEC C19, main switch with 10kA MCB, 32Amp, 1.8mtr cable length, 19" installation
152A-409A09N002X	09 Way PDU with C13 X 09, 3 x 32A 1P circuit breaker switch, IEC60309 plug (32A 3P+N+E), 3-meter cable length, Vertical Installation
1522-412A12N001X	12 Way PDU with IEC C13, main switch with 10kA MCB, 32Amp, 1.8mtr cable length, Vertical Installation
152A-412A12N002X	12 Way PDU with C13 X 12, 3 x 32A 1P circuit breaker switch, IEC60309 plug (32A 3P+N+E), 3-meter cable length, Vertical Installation
1529-224A18B062X	24 Way PDU with [C13 X 18 + C19 X 6], 16A main switch, IEC60309 plug (16A 2P+E), 3 mtr cable length, Vertical Installation
1529-424A18B062X	24 Way PDU with [C13 X 18 + C19 X 6], 32A main switch, IEC60309 plug (32A 2P+E), 3 mtr cable length, Vertical Installation
152A-224A18B062X	24 Way PDU with [C13 X 18 + C19 X 6], 16A main switch, IEC60309 plug (16A 3P+N+E), 3 mtr cable length, Vertical Installation
152A-424A18B062X	24 Way PDU with [C13 X 18 + C19 X 6], 32A main switch, IEC60309 plug (32A 3P+N+E), 3 mtr cable length, Vertical Installation
152A-430A24B062X	30 Way PDU with [C13 X 24 + C19 X 06], 32A main switch, IEC60309 plug (32A 3P+N+E), 3 mtr cable length, Vertical Installation
1522-230A24B064X	30 Way PDU with [C13X24+C19X6], 16A main switch, 2 mtr cable length, Vertical Installation