

CAT 6A UNSHIELDED PATCH PANEL BLANK TOOL LESS

Blank UTP Tool Less patch panel from Norden exceeds TIA and ISO component specifications, supporting network convergence protocols, delivering maximum bandwidth and extended reliability for all LAN, multimedia, and Power over Ethernet applications. Each port of the panel is numbered and has a designated label area for clear port identification. Keystone outlets can be snapped in to the 10" frame without the need for tooling of any type and is supplied in unloaded version.

The tool-less jack termination offers fast and reliable installation of unshielded cable, quick and easy in termination. A rear cable management bar is supplied which acts as a stress reliever of terminated cables. The patch panel comes with mini cable ties, cage nuts and rear cable management bar as standard. Enhanced cable retention fixture and unique assembly. Supports solid 22-24 AWG wires and stranded 24-26 AWG



COMPLIANCE

EEE 802.3an, IEEE 802.3af (PoE), IEEE 802.3at (PoE+)
 ISO/IEC 11281:2002, IEC 60603-7
 TIA-968-A (formerly FCC Part 68 Subpart F)

DESIGN & MATERIALS

Panel Type	Flat
Panel Style	Blank
Mounting Style	Tool Less (Module)
Panel Width	254 mm (10")
Panel Height	1U: 44.0 mm
Panel Depth	101.6 mm
Outlet Style	Unkeyed RJ-45
Outlets	12 Ports
IDC Contact	45° secure, gas tight connection
Connector Module Holder	High Impact, Flame-Retardant Plastic Compound, UL 94 V-0
Cover Colour and Material	Black, Powder Coated Steel
Re Termination	>20
Temperature	- 20°C to 60°C
Humidity	0-90% non-condensing

STANDARDS

Wiring Standards	EIA/TIA 568 A/B
Flammability rating	UL 94V-0
Safety Rating	UL1863
Transmission	ISO/IEC 11801:2002 ANSI /TIA/EIA-568.B.2-10

ORDERING INFORMATION

Part Number	Description
121-41T18012B	Category 6A Unshielded Patch Panel Blank Tool Less 12 Port

PACKING INFORMATION

Part Number	Packing Qty.	Packing Mode	N.W (kg)	G.W (kg)	Dimension (mm)
121-41T18012B	10 x 1	Carton Box	4.5	6.0	520 x 320 x 270