



# CATEGORY 6A U/UTP 23 AWG 4 PAIR CMR RATED FRPVC JACKET CABLE

Norden Category 6A U/UTP CMR cables exceed Category 6A/Class EA specification. It is tested to 500MHz frequency range and designed to support 10 Gigabyte applications to full 100m. Extremely high pair-balance providing excellent EMC (Electro Magnetic Compatibility), minimizing radiation, maximizing noise immunity and providing high alien cross talk performance to U/UTP (Unshielded Twisted Pair) cabling systems.



## COMPLIANCE

IEEE 802.3an :2006 (10GBASE-T)  
ANSI/TIA-568.2-D Category 6A ISO/  
IEC-11801, 2nd Edition Class EA IEC  
61156-5:2002 Category 6A

## PRODUCT CLASSIFICATION

Product Sequence	Premium
Product Type	Twisted Pair Cable

## MATERIAL CONSTRUCTION & DESIGN

Conductor Material	Bare Copper
Conductor Size	0.57 mm, 23 AWG
Conductor Construction	Solid
Insulation Material	HDPE
Insulation O.D.	1.02 ± 0.03 mm
Conductor Unit Identification	Solid/Stripe
Colour Code	Per TIA/EIA 568-B
Total Number of Wires	8
Rip Cord	Yes
Overall Drain-Wire Material	N/A
Overall Drain-Wire Size	N/A
Overall Drain-Wire Construction	N/A
Outer Jacket	FR PVC (CMR Rated)
Outer Jacket Thickness & Ex. Diameter	0.55±0.05 mm, 6.3±0.4 mm
Outer Jacket Colour	Per Requirement
Marking	Per Requirement

# CATEGORY 6A U/UTP 23 AWG 4 PAIR CMR RATED FRPVC JACKET CABLE

## ELECTRICAL & MECHANICAL CHARACTERISTICS

Frequency Range	1 - 500 Mhz
Characteristic Impedance	100±6Ω @ 1-500 MHZ
Coupling Attenuation	85 db min @ 30-100 MHz 85-20 log (f/100) @100-500 MHz
DC Resistance	72 Ω/km max.
Max. Resistance Unbalance	2 %
Capacitance	45 pF/m nom.
Capacitance Unbalance(Wire to Ground)	1500 pF/Km max.
Delay Skew	25 ns/100m max.
Velocity of Propagation	67 %
Dielectric Strength	1.5 KV/minute
Insulation Resistance	5000 MΩ•Km min
Short Term Bend Radius	8 x OD mm
Long Term Bend Radius	4 x OD mm
Operating Temperature Range	-20°C to +70°C

## TRANSMISSION PERFORMANCE

Cat. 6A Un-screened Pair Horizontal Cables\*

Freq. MHz	Attenuation dB/100m @ 20°C	NEXT dB	PS dB	NEXT	RL dB	ACR dB	ELFEXT dB	PSELFEXT dB
1	1.7	86.3	83.3		26.0	84.6	84.0	80.0
4	3.4	85.0	83.0		29.0	75.6	81.0	78.0
10	5.4	77.3	74.3		31.0	71.9	76.0	73.0
20	7.6	70.0	67.0		30.0	62.4	70.0	67.0
31.25	9.7	68.0	65.0		29.8	58.3	65.0	63.0
100	18.0	65.3	62.3		27.1	47.3	55.0	52.8
150	23.6	62.0	59.8		26.0	38.4	53.5	51.5
200	27.4	59.0	57.2		25.0	31.6	49.0	46.0
250	31.0	57.6	54.6		25.2	26.6	44.0	41.0
300	34.2	55.0	52.0		24.0	20.3	39.6	36.6
400	40.0	53.0	51.8		21.8	13.0	37.0	34.0
500	42.2	52.0	50.0		21.8	9.8	35.0	33.0

\*Supplied cables meets Cat. 6a min. transmission requirements as per IEC 61156-5 Ed. 2

## ORDERING INFORMATION

Part Number	Description	Standard Length
114-14704104X	Category 6A U/UTP 23 AWG 4 Pair CMR rated FRPVC Jacket Cable	305 mtr

X: BK(Black), BL(Blue), GN(Green), GY(Gray), RD(Red), WH(White), YL(Yellow)

## PACKING INFORMATION

Part Number	Packing Mode	N.W (kg)	G.W (kg)	Dimension (mm)
114-14704104X	Plywood Reel/Ctn	14.3	16.3	340 x 340 x 340