

## POWER DISTRIBUTION UNIT



NORDEN Power Distribution Units are designed and manufactured for cabinets. The product is equipped with sockets meeting different systems and standards. Products can be produced accordingly to customer's special requirement, the dimension can reach to 4600 mm. required for product installation.

### COMPLIANCE

EMC & safety:-EN 55022 Class A,EN 55024,EN 61000-3-2,EN 61000-3-3,FCC Part 15 Class A, ICES-003,PSE, VCCI Class A,VDE  
 Environmental: RoHS, REACH: Contains No SVHCs  
 Socket/Outlet Standard: BS1363  
 Cable plug: BS1363

### DESIGN & MATERIALS

Material of Construction	PC/ABS alloy, High Impact FR thermoplastic -UUL94-V0
Shell Material & Colour	Aluminium, black
Outlet Qty.	2 way
Power Input Style	Left end single input style
Bracket Installation Style	Frontal Installation Style
Control function	Switch
Lead length	1.8 mtr

### ELECTRICAL & ENVIRONMENTAL DATA

Current Rating	13A 250VAC
Maximum load current available in	13A
Input frequency	50 or 60 Hz
Maximum load capacity	4KW
Operating Environment	-5 °C to +45 °C
Operating Relative Humidity	5 – 95 %
Operating Elevation	0-3000 metres
Storage Temperature	-25 °C to +65 °C
Storage Relative Humidity	5 – 95 %
Storage Elevation	0-15000 metres

### ORDERING INFORMATION

Part Number	Description
133T-102E02N001X	2 Way PDU BS1363 UK Socket & Plug with main switch,13Amp, cable length 1.8mtr, 10" installation.

X: BK(Black)

### PACKING INFORMATION

Part Number	Packing Qty.	Packing Mode	N.W (kg)	G.W (kg)	Dimension (mm)
2 Way PDU	10 x 1	Carton Box	13.0	14.0	253x45x45