

CATEGORY 8 SHIELDED PATCH PANEL BLANK TOOL LESS 1U

Blank Shielded patch panel from Norden exceeds TIA and ISO component specifications, supporting network convergence protocols, delivering maximum bandwidth and extended reliability for all LAN, multimedia, and Power over Ethernet applications. Each port of the panel is numbered and has a designated label area for clear port identification. Keystone outlets can be snapped in to the 19" frame without the need for tooling of any type and is supplied in unloaded version. There is also an earth cable provided that has to be grounded for the proper functioning of the shielded system.

The tool-less jack termination offers fast and reliable installation of shielded cable, quick and easy in termination. A rear cable management bar is supplied which acts as a stress reliever of terminated cables. All performance parameters, including NEXT, FEXT Attenuation and Return Loss are designed to meet the Cabling standard. The patch panel comes with mini cable ties, cage nuts and rear cable management bar as standard.



COMPLIANCE

ANSI/TIA-568.2-D

ISO / IEC TR 11801-9901 : 2014 Category 8.

IEEE 802.3af PoE and IEEE 802.3at PoE+ applications.

DESIGN & MATERIALS

Panel Type	Flat
Panel Style	Blank
Mounting Style	Tool Less (Module)
Panel Width	483 mm (19")
Panel Height	44 mm, 1U
Panel Depth	79.5 mm
Outlet Style	Unkeyed RJ-45
Outlets	24 Ports
Angle	180 Degree
Connector Module Holder	High Impact, Flame-Retardant Plastic Compound, UL 94 V-0
Cover Colour and Material	Black, Powder Coated Steel

STANDARDS

Wiring Standards	EIA/TIA 568 A/B
Flammability Rating	UL 94V-0
Safety Rating	UL1863
Transmission	ISO / IEC TR 11801-9901 ANSI/TIA-568.2-D

ORDERING INFORMATION

Part Number	Description
121-72T18024B	Category 8 Shielded Patch Panel Blank Tool Less 24 Port

PACKING INFORMATION

Part Number	Packing Qty.	Packing Mode	N.W (kg)	G.W (kg)	Dimension (mm)
121-72T18024B	10 x 1	Carton Box	5.5	6.8	520 x 320 x 270