

# MAX-POWER SERIES

## 3kVA Online Transformerless UPS



Norden's Maxpower Series 3 kVA UPS is an online double conversion UPS that features a single phase in both input and output, and an output power factor of 0.9. This tower-type UPS is designed to be used in commercial buildings and offices, and can be connected to desktops and servers.



### General Features

- High power density
- Online double conversion with full digital control
- Selectable output voltage:220/230/240Vac
- Wide input voltage range:110~300Vac
- Input power factor 0.99 with PFC
- Maximum charging current up to 12A (long run unit)
- Emergency power off function
- ECO mode operation for energy saving
- Multiple communication interface:RS232 (USB/Dry contact/SNMP card optional)
- Self-testing when UPS start-up
- Generator compatible
- Cold start
- Intelligent fan speed regulation
- Outlet socket universal (optional)

### SPECIFICATIONS

MODEL		CN7003MPI/CN7003MPE		
Capacity	VA	3000		
	Watts	2700		
	Phase	Single phase with ground		
Input	Normal Voltage	208/220/230/240Vac		
	Operating Voltage Range	110~300Vac		
	Frequency Range	45~55Hz/55~65Hz (Auto-detect)		
	Power Factor	≥0.99 @Nominal voltage(100% load)		
Output	Output Voltage	208/220/230/240Vac		
	Power Factor	0.9		
	Voltage Regulation	±1%		
	Frequency	Line mode (Synchronized range)	45~55Hz / 56~64Hz	
		Bat. mode	50Hz / 60Hz ±0.1Hz	
	Crest Factor	3 : 1		
	Harmonic Distortion (THDv)	≤3% THD(Linear load)		
		≤5% THD(Non-linear load)		
	Transfer time	AC to DC	Zero	
		Inverter to bypass	4ms(Typical)	
Waveform	Pure sinewave			
Efficiency	AC mode	91%		
	Battery mode	88%		
Battery	Internal	Battery type	12V/9AH	
		Numbers	6	
		Typical recharging time	4 hours recover to 90% capacity	
		Charging current(max.)	1.0A	
		Charging voltage	82.2Vdc ±1%	
	External	Battery Numbers	6	8
		Charging Voltage	82.2Vdc ±1%	109.6Vdc ±1%
		Backup time	6A/12A	6A/12A

# MAX-POWER SERIES

## 3kVA Online Transformerless UPS



MODEL		CN7003MPI/CN7003MPE	
Indicators	LCD	Load level, Battery level, AC mode, Battery mode, Bypass mode, and Fault indicators	
Alarm	Battery mode	Beeping every 4 seconds	
	Battery low	Beeping every second	
	Overload	Beeping twice every second	
	Fault	Continuously beeping	
Physical	Dimension W x D x H (mm)	Standard model	191x460x337
		Long run model	191x460x337
	Weight (kg)	Standard model	25
		Long run model	10
Environment	Humidity	20-90% RH @ 0-40°C (Non-condensing)	
	Noise level	<50dB @ 1 Meter	
Management	Smart RS232/USB	Supports Windows® 7/8/10, Linux, FreeBSD and MAC	
	Optional SNMP	Power management from SNMP manager and web browser	
Standards	Safety	IEC/EN62040-1, IEC/EN62477-1	
	EMC	IEN/EN62040-2, IEC61000-4-2, IEC61000-4-3, IEC61000-4-4, IEC61000-4-5, IEC61000-4-6, IEC61000-4-8	

\*Specifications are subject to change without prior notice.

### EXTERNAL BATTERY PACK

MODEL		CNBC00396CT
BATTERY SYSTEM		
Battery type	VRLA (Lead acid maintenance free battery)	
Typical battery recharging time	6~8 hours (to 90% of full capacity)	
Typical battery life	3~5 years, depend on discharging cycle and ambient temperature	
System voltage	96Vdc	
Charging current (Max)	1.4A	
Battery quantity	16	
Capacity	9Ah/12V (7Ah/12V optional)	
PHYSICAL		
Dimension W x D x H (mm)	191 x 460 x 337	
Net weight (kg)	47.5	
ENVIRONMENT		
Safety	CE	
Operating environment	0°C~40°C	
Relative humidity	0~95% (Non condensing)	
Noise level	<40dB at 1 Meter	

### ORDERING INFORMATION

Part Number	Description
CN7003MPI	3kVA Online Transformer-less UPS (Internal Battery)
CN7003MPE	3kVA Online Transformer-less UPS (External Battery)
CNBC00396CT	96VDC Tower Mount Battery Pack

### COMPATIBLE ACCESSORIES

Part Number	Description
CNS02	Mini SNMP Card for 1-10kVA UPS