

# MAX-POWER SERIES

## Online Transformerless 15kVA UPS

Maxpower Series is a small to medium power transformer-less UPS of CellNor. This is an online double conversion UPS with power factor of 0.9. The CN7315MP model supports ECO operation mode.



### General Features

- Online double conversion with DSP control
- Wide input range:208~478Vac
- Wide input frequency range:40~70Hz
- Support parallel function(Optional)
- Optimization battery group, the quantity of battery:16/18/20pcs
- Support 3/1 and 1/1 operation
- Maximum charging current up to 16A(Settable)
- ECO mode operation for energy saving
- Cold start
- Intelligent fan speed regulation
- Self-testing when UPS start-up

### SPECIFICATIONS

MODEL		CN7315MP	
Capacity	VA	15000	
	Watts	13500	
Input	Normal Voltage	380/400/415Vac; (3Ph+N+PE) 220/230/240Vac (L+N+PE)	
	Operating voltage range	208~478Vac; 120~276Vac	
	Operating frequency range	40~70Hz (50/60Hz Auto-Sensing)	
	Power factor	≥0.99	
	Bypass voltage range	Max.voltage: 220V: +25%(optional +10%,+15%,+20%) 230V: +20% (optional +10%,+15%) 240V: +15% (optional +10%) Min.voltage: -45% (optional -20%,-30%)	
	Bypass frequency range	Frequency protection range:±10%	
Output	Generator input	Support	
	Rated voltage	220/230/240Vac	
	Power factor	0.9	
	Voltage regulation	±1%	
	Frequency	Line mode	±1%/±2%/±4%/±5%/±10% of the rated frequency(optional)
		Bat. mode	50/60(±0.1)Hz
	Crest factor	3:1	
	Harmonic distortion (THDv)	≤2% with linear load, ≤5% with non-linear load	
	Efficiency	>94%	
Battery	Battery voltage	192/216/240Vac	
	Capacity (Standard unit)	12V/7Ah/9Ah	
	Typical recharging time	6~8 hours (to 90% of full capacity)	
	Charging current	2.7A standard unit) ; Max.current 16A(Long run unit)	

# MAX-POWER SERIES

## Online Transformerless 15kVA UPS

MODEL		CN7315MP	
System Features	Transfer time	Mains to battery:0ms; Mains to bypass:0ms	
	Overload	Line mode	Load≤110%: last 60min, ≤125%: last 10min, ≤150%: last 1min, >150% turn to bypass mode immediately
		Bypass mode	100A(Breaker)
	Short circuit	Hold whole system	
	Overheat	Line mode: Turn to bypass; Backup mode: shut down UPS immediately	
	Battery low	Alarm and switch off	
	Self-diagnostics	Upon power on and software control	
	Battery	Advanced battery management	
	Audible & Visual alarms	Line failure, Battery under voltage, Overload, System fault	
	LED & LCD display	Line mode, Bat. mode, Eco mode, Bypass mode, Battery under voltage, Overload & UPS fault	
	LCD display	Input voltage, Input frequency, Output voltage, Output frequency, Load percentage, Battery voltage, Inner temperature & Remaining battery backup time	
	Communication interface	Rs232, USB, SNMP card (optional), Parallel board (optional), Relay card (optional)	
Environment	Operating temperature	0~40°C	
	Storage temperature	-25~55°C	
	Humidity range	0~95% (Non-condensing)	
	Altitude	<1500m	
	Noise level	<55dB at 1 Meter	
Physical	Dimension	E: 220 x 531 x 450 ; l:250 x 900 x 868	
	Weight	24/167	

STANDARDS	
Safety	IEC/EN62040-1, IEC/EN60950-1
EMC	IEC/EN62040-2, IEC61000-4-2, IEC61000-4-3, IEC61000-4-4, IEC61000-4-5, IEC61000-4-6, IEC61000-4-8

### ORDERING INFORMATION

Part Number	Description
CN7315MP	15kVA Medium Power Transformerless UPS

