

DP BOX EXTERNAL

The box can be mounted with 10,20,30,50,100 pair LSA disconnection module. Waterproof box suit external wire distribution. The box is with key lock.



MATERIAL

Material of Plastic Parts	ABS
Material of Back Mounting	1mm Thickness Stainless steel

ELECTRICAL PERFORMANCE

Insulation resistance	≥ 500mΩ / 500V [DC]
Resistance to voltage:	No Breakdown or Arc for 1 minute under 1kV [AC]

ENVIRONMENT

Environment condition	-40°C — 90°C
Operation condition	-20°C — 80°C
Atmospheric pressure	70-106KPa
Relative humidity	< 85% (+30°C)

ORDERING INFORMATION

Part Number	Description	Size (mm)
223-212P0010	10 Pair External Distribution Point Box with Key Lock	215 x 85 x 135
223-212P0020	20 Pair External Distribution Point Box with Key Lock	215 x 85 x 135
223-212P0030	30 Pair External Distribution Point Box with Key Lock	215 x 85 x 135
223-212P0050	50 Pair External Distribution Point Box with Key Lock	220 x 95 x 190
223-212P0100	100 Pair External Distribution Point Box with Key Lock	400 x 120 x 195

PACKING INFORMATION

Part Number	Packing Qty.	Packing Mode	N.W (kg)	G.W (kg)	Dimension (mm)
223-212P0010	30 x 1	Carton Box	17.5	18.5	510 x 490 x 450
223-212P0020	30 x 1	Carton Box	17.5	18.5	510 x 490 x 450
223-212P0030	30 x 1	Carton Box	17.5	18.5	510 x 490 x 450
223-212P0050	25 x 1	Carton Box	20.0	21.0	690 x 450 x 420
223-212P0100	10 x 1	Carton Box	13.5	14.5	640 x 410 x 420