

2MP 44X STARLIGHT NETWORK PTZ DOME CAMERA



ENC-HHP5Z-250R-13

FEATURES

Starlight Illumination

Smart IR Up to 250m (820ft)

16X Digital Zoom

44X Optical Zoom

Onvif (Profile S/G/T)

Triple Stream

Electronic Image Stabilization

IP66



SPECIFICATION

MODEL	Model No.	ENC-HHP5Z-250R-13
	Type	2MP 44X Starlight Network PTZ Dome Camera
CAMERA	Sensor	1/2.8", 2.0 megapixel, progressive scan, CMOS
	Lens	5 ~ 220mm, AF automatic focusing and motorized zoom lens
	Angle of View (H)	60.6° ~ 1.8°
	Angle of View (V)	34.8° ~ 0.8°
	Angle of View (O)	74.5° ~ 2.1°
	Shutter	Auto/Manual; shutter time: 1 ~ 1/100000s
	Minimum Illumination	Colour: 0.002Lux (F1.2, AGC ON) ; B/W: 0Lux with IR
	Day/Night	IR-cut filter with auto switch (ICR)
	S/N	>52dB
	IR Range	Up to 250m (820ft)
	Wavelength	850nm
	Defog	Digital Defog
	WDR	120dB
	Digital Zoom	16x
Optical Zoom	44x	



2MP 44X STARLIGHT NETWORK PTZ DOME CAMERA



ENC-HHP5Z-250R-13

MODEL	Model No.	ENC-HHP5Z-250R-13
	Type	2MP 44X Starlight Network PTZ Dome Camera
VIDEO	Video Compression	H.265+, H.265, H.264, MJPEG
	H.264 code profile	Baseline profile, Main Profile, High Profile
	Frame Rate	Main Stream: 2MP (1920*1080), Max 60fps; Sub Stream: 2MP (1920*1080), Max 60fps; Third Stream: D1 (720*576), Max 60fps
	OSD	Up to 8 OSDs
	Privacy Mask	Up to 24 areas
	ROI	Up to 8 areas
	Motion Detection	Up to 4 areas
	Digital noise reduction	2D/3D DNR
	Smart IR	Supported
	HLC	Supported
BLC	Supported	
AUDIO	Audio Compression	G.711
	Two-way Audio	Supported
	Suppression	Supported
	Sampling Rate	8KHZ
SMART	Behavior Detection	Intrusion, Crossing line
	Intelligent Identification	Abandoned Object, Missing Object
	Statistical Analysis	Face detection, Audio detection, Motion detection, People counting, Master-slave Linkage
	Auto Tracking	Supported
	General Function	Watermark, IP Address Filtering, Tampering Alarm, Alarm input, Alarm output, Access Policy, ARP Protection, RTSP Authentication, User Authentication
INTERFACE	Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS
	Compatible Integration	ONVIF (Profile S, Profile G, Profile T), API
	Client	Eyenor VMS
	Web Browser	Plug-in required live view: IE9+, Chrome 41 and below, Firefox 52 and below Plug-in free live view: Chrome 57.0+, Firefox 58.0+, Edge 16+, Safari 11+
	Edge Storage	Micro SD, up to 256GB
	Network Storage	ANR
	Network	1 RJ45 10M/100M Base-TX Ethernet
	Audio I/O	1/1
	Audio Voltage	Audio cable;1 Input: impedance 35kΩ; amplitude 2V [p-p];1 Output: impedance 600Ω; amplitude 2V [p-p]
	Alarm I/O	2/1
	Built-in Mic	N/A
	Built-in Speaker	N/A
PAN AND TILT	Pan Range	360° (endless)
	Pan Speed	0.1°/s ~ 240°/s
	Preset speed	300°/s
	Tilt Range	-15° ~ 90° (auto reverse)
	Tilt Speed	0.1° ~ 160°/s
	Tilt Preset speed	240°/s
	Number of Presets	1024
	Patrol	Preset patrol, Route patrol, Recorded patrol
GENERAL	Power	AC 24V±25% (Default), DC 24V±25%
	Power consumption	16 ~ 56W
	Dimensions (Ø x H)	Φ270 x 496.7mm (Φ10.6" x 19.6")
	Weight	9.69kg (21.4lb)
	Working Environment	-40°C ~ 70°C (-40°F ~ 158°F), Humidity: ≤95% RH (non-condensing)
	Surge Protection	Supported
	Ingress Protection	IP66
	Vandal Resistant	N/A
Reset Button	Supported	




2MP 44X STARLIGHT NETWORK PTZ DOME CAMERA



ENC-HHP5Z-250R-13

MODEL	Model No.	ENC-HHP5Z-250R-13
	Type	2MP 44X Starlight Network PTZ Dome Camera

Dimension Unit : mm



ORDERING INFORMATION

Part Number	Description	Standard Quantity
ENC-HHP5Z-250R-13	2MP Starlight IP H.265 High Speed PTZ dome camera with 44X Optical zoom, WDR, Micro SD card slot, Smart analytics and 250M IR support	1

PACKING INFORMATION

Part Number	Packing Mode	Gross weight(Kg)	Dimension(mm)
ENC-HHP5Z-250R-13	Carton Box	9.69kg (21.4lb)	Φ270 × 496.7mm (Φ10.6" × 19.6")

