

160-200kVA Double Conversion Transformer-less UPS

Norden's Ultra power series 160-200 kVA UPS is an online double conversion UPS that has three-phase in both input and output and a unity output power factor. This features a maximum parallel expanded operation of up to 6 units and has an inverter efficiency upto 96% makes it suitable for data center applications.



General Features

- Wide input voltage range 140~485Vac (Phase voltage 80~280Vac)
- High input power factor, can be up to 0.99
- Three-level inverter topology, the efficiency can be up to 96%
- Support parallel expanded operation: maximum is 6 units
- Input current harmonic:<3%
- Large charging current
- High adaptability for the load it can connect full inductive load or capacitive load
- Power Walk in function, it can reduce the star current impact to the system and reduce the capacity of the generator
- Optimized battery group, the quantity of battery:30-50pcs
- LBS function can realize 2 independent UPS systems work in synchronization enhancing the reliability of the system
- The output factor is 1.0, and can be meet 100% unbalanced load
- Support USB,RS485,RS232,SNMP,dry contact card

SPECIFICATIONS

MODEL		CN933160U / CN933160U-5L	CN933180U / CN933180U-5L	CN933200U / CN933200U-5L	
Capacity	kVA	160	180	200	
	kW	160	180	200	
Input	Normal Voltage	380/400/415Vac (3Ph+N+PE)			
	Operating voltage range	140~485Vac for 40% Load; 305~485Vac for Full Load			
	Harmonic distortion(THDi)	<3%(100% linear load)			
	Operating frequency range	40~70Hz			
	Power factor	≥0.99			
	Bypass voltage range	220Vac Max.Voltage:+25% (optional +10%,+15%,+20%) 230Vac Max.Voltage:+20%(optional +10%,+15%) 240Vac Max.Voltage:+15%(optional +10%) Min.Voltage:-45%(optional -20%,-30%)			
	Bypass Frequency range	Frequency synchronize tracing range:±10%			
Output	Generator input	Yes			
	Rated voltage	380/400/415Vac (3Ph+N+PE)			
	Power factor	1.0			
	Voltage regulation	±1%			
	Frequency	Line mode	±1%/±2%/±4%/±5%/±10% of the rated frequency (Optional)		
		Bat. mode	50/60(±0.1)Hz		
	Crest factor	3:1			
	Harmonic distortion (THDv)	≤2% with linear load, ≤4% with non-linear load			
	Efficiency	96%			
	Output Waveform	Pure Sine Wave			
Battery	Battery voltage	±180/±192/±204/±216/±228/±240/±252/±264/±276/±288/±300Vdc(30/32/34/36/38/40/42/44/46/48/50pcs)			
	Charging current (Charging current can be set according to the battery capacity installed)	60A		80A	

MODEL		CN933160U / CN933160U-5L	CN933180U / CN933180U-5L	CN933200U / CN933200U-5L
System Features	Transfer time	Mains to battery:0ms; Mains to bypass:0ms		
	Overload	Line mode	≤110%: Overload 60min, ≤150%: Overload 1min, >150% turn to bypass mode immediately	
		Bypass mode	135% Overload long time; 170% Overload 100ms	
	Backfeed Protection	Yes		
	Alarm	Overload, utility abnormal, UPS fault, battery low, etc		
	Protection	Short circuit, overload, over-temperature, battery low, fan fault alarm		
	Remote LCD	Yes		
Communication	USB, RS232, RS485, Parallel port,dry contact, Intelligent slot, LBS, SNMP card (optional), Relay card (optional)			
Environment	Operating temperature	0-40°C		
	Storage temperature	-25-55°C		
	Humidity range	0-95% (Non-condensing)		
	Altitude	<1500m		
Physical	Noise level	<63dB	<64dB	<66dB
		Dimension W x D x H (mm)	850x442x1200	850x600x1600
	Net Weight (kg)	200	220	280
Standards	Safety	IEC/EN62040-1,IEC/EN60950-1		
	EMC	IEC/EN62040-2,IEC61000-4-2,IEC61000-4-3,IEC61000-4-4,IEC61000-4-5,IEC61000-4-6,IEC61000-4-8		

*Specifications are subject to change without prior notice.

ORDERING INFORMATION

Part Number	Description
CN933160U	160kVA Double Conversion Transformer-less 3/3 UPS (External Battery)
CN933160U-5L	160kVA Double Conversion Transformer-less 3/3 UPS with 5inch LCD display (External Battery)
CN933180U	180kVA Double Conversion Transformer-less 3/3 UPS (External Battery)
CN933180U-5L	180kVA Double Conversion Transformer-less 3/3 UPS with 5inch LCD display (External Battery)
CN933200U	200kVA Double Conversion Transformer-less 3/3 UPS (External Battery)
CN933200U-5L	200kVA Double Conversion Transformer-less 3/3 UPS with 5inch LCD display (External Battery)

COMPATIBLE ACCESSORIES

Part Number	Description
CNS01	SNMP Card for 10-80kVA 3/1 and 3/3

