


2 Core 12 AWG Unshielded Multi Conductor Cable

The Unshielded Multi Conductor Cable from NORDEN is suitable to use within Commercial Audio Systems, Control and Instrumentation purpose. The cable is constructed with PE insulation, Nylon Rip Cord and PVC or LSZH Outer Jacket.



CABLE CONSTRUCTION

Conductor
Bare Copper

Outer Jacket
PVC/LSZH

Jacket Color
Grey

Insulation
PE

Rip Cord
Nylon

PHYSICAL CHARACTERISTICS


Characteristic	Value
No. of Conductor	2
Conductor Size	12 AWG 19 x 25
Insulation Thickness	0.28 mm
Nom. Jacket Thickness	0.44 mm
Nom. Outer Cable Diameter	6.6 mm
Max. Recommended Pulling Tension	677 N
Min. Bending Radius Minor Axis	52.8 mm
Operating Temperature	-10°C to +75°C

ELECTRICAL CHARACTERISTICS

Characteristic	Unit	Value
Nom. Capacitance Cond. to Cond.	pF/m	78.6
Nom. Conductor DC Resistance	Ω/km	5.2
Max. Recommended Current @ 25°C	Amps	12
Max. Operating Voltage UL	V/min	300

MECHANICAL CHARACTERISTICS

Characteristic	Value
Test Material	PVC/LSZH
Before Tensile Strength (Mpa)	≥ 13.8
Aging Elongation (%)	≥ 100
After Tensile Strength (Mpa)	≥ 10.35
Aging Elongation (%)	≥ 75
Cold Bend (-20±°C x 4 hrs)	No Crack



2 Core 12 AWG Unshielded Multi Conductor Cable



INSULATION COLOUR CODE

Individual Core	Colour
Core 1	Black
Core 2	White

ORDERING INFORMATION

Part Number	Description	Net Weight (Kg/Km)
71-3102121	2 Core 12 AWG Unshielded Multi Conductor Cable PVC, 305m	80.2
71-3102122	2 Core 12 AWG Unshielded Multi Conductor Cable LSZH, 305m	84.3