

POWER DISTRIBUTION UNIT-UK SOCKET/UK PLUG



NORDEN Power Distribution Units are designed and manufactured for cabinets. The product is equipped with sockets meeting different systems and standards. Products can be produced accordingly to customer's special requirement, the dimension can reach to 4600 mm. required for product installation.

COMPLIANCE

EMC & safety:-EN 55022 Class A,EN 55024,EN 61000-3-2,EN 61000-3-3,FCC Part 15 Class A, ICES-003,PSE, VCCI Class A,VDE
 Environmental: RoHS, REACH: Contains No SVHCs
 Socket/Outlet Standard: BS1363
 Cable plug: BS1363

DESIGN & MATERIALS

Material of Construction	PC/ABS alloy, High Impact FR thermoplastic -UL94-V0
Shell Material & Colour	Aluminium, black
Outlet Qty.	6 way, 8 way, 10 way,12 way, 15 way
Power Input Style	Left end single input style
Bracket Installation Style	Frontal Installation Style
Control function	13 Amp
Monitor	LED (Optional)
Input	3 x 1.5MM3 3mtr UK Plug
Lead length	1.8 m, 3 m, 5 m (other cable length available on request)

ELECTRICAL & ENVIRONMENTAL DATA

Current Rating	13A , 250 VAC
Maximum load current available in	13A
Input frequency	50 or 60 Hz
Maximum load capacity	4KW
Operating Environment	-5 °C to +45 °C
Operating Relative Humidity	5 - 95 %
Operating Elevation	0-3000 metres
Storage Temperature	-25 °C to +65 °C
Storage Relative Humidity	5 - 95 %
Storage Elevation	0-15000 metres

POWER DISTRIBUTION UNIT-UK SOCKET/UK PLUG

ORDERING INFORMATION

Part Number	Description
13 Amp PDU	
1581-106E06N002X	6 Way UK Socket PDU With MCB,13Amp, 19" installation, UK Plug with 3 mtr Cable Length

PACKING INFORMATION

Part Number	Packing Qty.	Packing Mode	N.W (kg)	G.W (kg)	Dimension (mm)
6 Way PDU	10 x 1	Carton Box	13.0	14.0	510 x 190 x 310