

Standalone Metal Access Control

NAC-5101SA is a Single door multifunction Standalone access controller. It can support EM or MF card type upto 2000 users attendance registration. It may be mounted in severe conditions both indoors and outdoor capabilities. It includes a Backlit keypad, Wiegand output and Lock output current short circuit protection.

Application

Office areas, schools, communities, office buildings, hotels, shopping malls, shops, public service places, etc.

Features

- IP68 rating
- Anti-vandal, metal structure design
- Digital backlit keyboard
- Can be used as a Standalone keypad
- With WG26 output/input
- Supports different access ways: Entry by Card/Password/Card + Password
- Built-in buzzer
- Red, Yellow and Green LEDs displays the working status




Technical Parameters

Card Type	EM or MF
Working Frequency	125KHz or 13.56MHz
Capacity	2000 users
Lock Output	≤3A
Alarm Output	Yes
Working Voltage	DC 12V
Standby Current	≤30mA
Output Short Circuit Protection Time	≤100μS
Card Reading Distance	2~5cm
Door Opening Time	0~99s(Adjustable)
Working Humidity	10% ~ 90%
Working Temperature	-45°C ~ +60°C
Dimensions	120x56x18 mm
Weight	0.45Kg

Standalone Metal Access Control

Dimensions:



Ordering Information

Part Number	Description
NAC-5101SA	Standalone Metal Access Control