

FIBRE OPTIC MINI CLOSURE

Fibre optic mini splice closure provide space and protection for the fibre optic cable splicing and joint. They are perfect sealed design to be waterproof & dust-proof and suitable for pole mounted and wall mounted application.



MAIN FEATURES

- Out door use waterproof IP65, Light weight, small size, easy installation.
- Can install both PLC splitter and adapter(SC,FC,LC,ST....).
- High quality ABS plastic material.
- Used in strength and branch application for cables of bunchy fibre and ribbon fibre.
- Trays can be increased or reduced according to the application.
- Perfect outline, thunder, erosion & aging resistance.
- Strong and reasonable structure with mechanical sealing structure filled with silicon rubber material, it can be opened after sealing and can be reused.

TECHNICAL PARAMETERS:

Environmental temperature	-40 to + 85°C
Atmospheric pressure	70-106 Kpa
Intensity	15 KV(DC) not being broken down,has no flying arc.
Components	Seal tape, Insulation tape, Nylon tie, optical cable heat shrinkable sleeve, mental hook, seal fittings, numeral bar, retaining ring
Span-life	More than 20 years

ORDERING INFORMATION

Part No.	Cable Port	Splice Tray/Max Core	PLC Splitter	Adapter plater	Dimension (include cable port) (mm)
551-2100X	2	4/48 Core			285 x 200 x 90
551-3100X	3	4/48 Core			285 x 200 x 90
551-3211X	3	2/24	1*8, 1*16	18core(Flip over)	285 x 200 x 90
551-2211X	2	2/24	1*8, 1*16	18core (Fixed)	285 x 200 x 90
551-3211X	3	2/24	1*8, 1*16	18core (Fixed)	285 x 200 x 90