

SPECIFICATION

MODEL	Model No.	ENC-HBU5M-40R-69
	Type	2MP H.265 IR IP Bullet Camera
CAMERA	Image Sensor	1/2.8" Progressive Scan CMOS
	Min. illumination	Color 0.01Lux;IR ON 0 Lux
	Day/Night	ICR
	Shutter Speed	1/5-1/20000
	Auto Iris	Yes
	Wide Dynamic Range	WDR>120dB
	Digital Noise Reduction	2D/3D
	Lens	2.8-12mm (Motorized lens)
	FOV	95°~35°C
	IR LED	17pcs
IR Range	40M	
IMAGE	Video Compression	H.264/265, MJPEG
	Bit Rate (CBR/VBR)	Main stream: 500kb-12000kb; Sub stream: 100kb-6000kb
	Audio Compression	G.711, RAW_PCM
	Max. Resolution	1920x1080/30fps
	Stream	Stream1: 1920x1080/1280x720; Stream 2: D1 to QVGA
	Image Setting	Rotate Mode, Saturation, Brightness, Contrast, Sharpness
	HLC	Yes
	9:16 Corridor mode	Yes
	DIS	Auto
	ROI	Yes
	Defog	Yes
	NETWORK	Network Protocols
Alarm Trigger		Motion Detection, Line Crossing, Tamper, Area Intrusion, Camera Move, Dwell, Multiple Dwell, Retrograde Detection, Object Left, Object Remove, Abnormal Speed, Illegal Parking, Network disconnect, Disk alarm, I/O alarm
RTSP Video		Standard RFC2326, Support QuickTime / VLC Player.
Security		User security authentication, Reset, Hardware WatchDog
Web Language		English, Polish, Italian, Portuguese, Spanish
System Compatibility		Onvif, CGI
INTERFACE	Ethernet	1 Ethernet (10/100 Base-T) RJ-45 Connector
	Audio I/O	1ch Audio In & 1ch Audio Out
	Alarm I/O	1ch Alarm In & 1ch Alarm Out
	RS485	Yes
	BNC Output	Yes
	Reset Button	Yes
	Edge Storage	Micro SD/SDHC/SDXC slot, Max 128GB
GENERAL	Power Supply	DC 12V/PoE
	Power Consumption	5W (IR LED OFF); 8W (IR LED ON)
	Operating Temperature	Working Temperature:-40°C ~ 60°C (-40°F ~ 140°F)
	Operating Humidity	0% - 90% RH
	Ingress Protection	IP66, IK10
	Dimensions	110x110x377mm
Weight	1.68Kg	