

# Fireproof Ceiling Speaker



## DESCRIPTION

The NVS-10230006CS is a Fireproof Ceiling Speaker. It is made of high-quality engineering plastic, which assure a long-term durability and never out of shape and it will not color fade. The electric wire connecting terminal is better protected with a fireproof hood.

## FEATURES

- Complied with EN54-24 Requirements
- Three speaker line terminals are available, each with a different power rating.
- Equipped with thermal fuse for protection
- Ceramic connection port for speaker cable
- Fireproof plastic speaker dome
- Frameless aluminum mesh, never rust

## Specifications

Model	NVS-10230006CS
Rated Power	6W
Driver Size	6" x1
Frequency Response	90Hz-18KHz
Input Voltage/Impedance	100V
Power Taping Options	1.5/3/6W
Coverage angle 1kHz(HxV)	180°
Ways/Speakers/Type	1 way, double cone full range Ø156mm, 100V system
Connections	Ceramic connector and thermal fuse
Sensitivity(1m,1w)	91dB
Maximum SPL(1m)	99dB
Weight	1Kg
Dimension	Ø190x108mm
Hole diameter	Ø168-172mm

## ORDERING INFORMATION

Part Number	Description	Standard Quantity
NVS-10230006CS	Fireproof Ceiling Speaker	1