

INTELLIGENT AUTOMATIC TRANSFER SWITCH



Norden Intelligent Automatic Transfer Switch helps in monitoring total load current and also system operating state. It has system-defined and user-defined alarming methods, which include audible and visual alarm, email alarm and the SNMP send trip alarm status information.

Other features are it save the system operation and alarm record which can be inquired and exported. The intelligent automatic transfer switch has single user operating system and supports software upgrade.

FEATURES

Monitor

- Monitors total load current
- Monitors input/output voltage
- Monitors Power supply A/B and system operating state

Remote Control

- Switch over power A and power B
- Threshold of total load current

Alarming

- System-Defined alarming: When current overload, automatic transfer happens and either power supply goes wrong
- User-defined alarm: Threshold of total load current+
- Alarming methods: Audible and visual alarm(external connection), Email alarm, and SNMP send trip alarm status information

Access method

- Web, accessing through IE
- SNMP, through standard network working station
- SERIAL (Modbus protocol and hyper terminal protocol)

System Configuration

- Time setting
- Button lock
- Voltage range setting
- Transfer time from secondary power supply to main

Other features

- Save the system operation and alarm record which can be inquired and exported.
- Single user operating system, support software upgrade

Environmental

- Temperature (Operating / Storage) 0 ~ 45°C / -20 ~ 70°C
- Humidity (Operating / Storage) 5 ~ 95% RH / 5 ~ 95% RH Non-condensing

INTELLIGENT AUTOMATIC TRANSFER SWITCH

INPUT

Input voltage	250V
Input current	16A
Input standard	IEC C20 Socket *2
Cable specification	C19/ BS1363 plug with 3x1.5mm ² cable 2PCS
Cable length	3m

OUTPUT

Output voltage	250V
Output current	C13(10A), C19(16A)
Outlet quantity	C13(8 ways), C19(2 ways)

PHYSICAL

Dimension (HxWxD)	482.6x220x44.4mm
-------------------	------------------

ORDERING INFORMATION

Part Number	Description
16 Amp PDU	
1551-210A08B022X	10Way (C13x8 + C19x2), 16Amp PDU with BS1363 Plug, Intelligent Automatic Transfer Switch, 3mtr cable length.