

FLOOR STANDING IP55 EXTERNAL CABINET WITH 120W DC HEAT EXCHANGER



The Easycab range of floor standing cabinet IP55 with 120W DC heat exchanger is designed for external telecommunication purpose. The smart design and professional engineering provides easy installation and maintenance. It is complywith GB/T 19183 and IEC 61969.

FEATURES

- Double wall type design with 120W DC heat exchanger
- Bolts are fixed inside, no trace design
- Rain awnings on top
- Bottom wire path, cover with rubber
- Front door with handle lock, extra space for AC if needed
- With 20cm height plinth / IP55 without fans With earthing /with 1 fixed shelf

Material	Double layer Galvanized sheet
Deg. of Protection	IP55
Surface finish	Degrease, acid pickling, rust prevention and parkerizing, pure water cleaning, static electricity plastic painting
Loading capacity	800 Kg
Material thickness	Mounting Rails: 2.0mm, Others: 1.5-2.0mm
Operation Temperature	-40°C to +55°C
Relative Humidity	Less than or equal to 95 percent (+35°C)
Atmospheric Pressure	70KPa to 106Kpa

ACCESSORIES

No.	Item	600 wide	800wide	Materials	Treatment	Note
1.	Frame	2	2	2.0mm galvanized steel	Powder coating	
2.	Front Door	1	1	1.5mm galvanized steel	Powder coating	with file box
3.	Side Door	2	2	1.5mm galvanized steel	Powder coating	Unremovable
4.	Back Door	1	1	1.5mm galvanized steel	Powder coating	
5.	Lock	1	1	\	\	Handle Lock
6.	Top cover	1	1	1.5mm galvanized steel	Powder coating	With water proof panel
7.	Door seal	1	1	Black Rubber	\	
8.	Door knob	1	1	galvanized steel T=1.5	GE	
9.	Release fastener	\	6 or 12	galvanized steel=1.5	Powder coating	H≤27U, 6pcs
10.	Bottom panel	1	1	galvanized steel=1.5	Powder coating	
11.	Mounting angle	6	6	galvanized steel=1.5	Powder coating	H≤27U, 4pcs
12.	Mounting profile	4	4	galvanized steel=2.0	Zinc plated	
13.	Plinth	1	1	galvanized steel=2.0	Powder coating	L=10 to 20 cm

FLOOR STANDING IP55 EXTERNAL CABINET WITH 120W DC HEAT EXCHANGER

ORDERING INFORMATION

Part Number	Description	Capacity (U)	Dimension (mm)
132K-1BS722X	Double layer Galvanized Sheet Floor Standing IP55 External Cabinet with 120W DC Heat Exchanger	22	650x700x1100

X: R1(RAL 9004), R2(RAL 7035), R3(RAL 9010)

PACKING INFORMATION

Part Number	Packing Qty.	Packing Mode	N.W (kg)	G.W (kg)	Dimension (mm)
132K-1BS722X	1 x 1	Carton + Wooden pallet	100	110	650x700x1200