# 8CH EMBEDDED NETWORK VIDEO RECORDER **EYENOR**®





## **ENR-02008-N-MPK**

### **FEATURES**

8 Channel Input Support H.265+, H.265, H.264 Video Formats HDMI and VGA Simultaneous Output ONVIF Profile (S, G, T) PoE Support





















#### **SPECIFICATION**

J. L	ST Edition 101						
DEL	Model No.	ENR-02008-N-MPK					
MODEL	Туре	8CH EMBEDDED NETWORK VIDEO RECORDER					
VIDEO & AUDIO	Video Input	8-Ch (Upgradable to 10 Channels)					
	Incoming Bandwidth	120 Mbps					
	Outgoing Bandwidth	100 Mbps					
	HDMI / VGA Output	HDMI 1: 3840×2160, 2560×1440, 1920×1080, 1440×900, 1280×800, 1280×720, 1024×768 VGA 1: 1920×1080, 1440×900, 1280×800, 1280×720, 1024×768					
	Audio Input / Output	1-Ch Input (3.5 mm) / 1-Ch Output (RCA)					
	Two-way Audio	Supported					
	Screen Split	1/2/3/4/5/6/7/8/9/10					
	Video Encryption	Supported					
	OSD Type	Title, Week, Date, Time, Text with different colors and adaptable sizes					
	Video Compression	H.265+, H.265, H.264					
	Video Bit Rate	32 kbps ~ 16 Mbps (per channel), CBR, VBR					
<u> </u>	Audio Compression	G.711A/G.711U					
CODING	Audio Bit Rate	8 kbps ~ 48 kbps					
8	Recording Resolution	8MP/6MP/5MP/3MP/1080P/UXGA/720P/VGA/4CIF/DCIF/2CIF/CIF/QCIF					
DE	Recording Mode	Continuous, Manual, Event (Pre/Post, Motion etc.), Schedule, ANR, Record Interval by Time / Size					
	Pre/Post Record Time	Pre (5~60 sec); Post (10~600 sec)					
	Fisheye Camera	N/A					
	De-warping	N/A					

# 8CH EMBEDDED NETWORK VIDEO RECORDER **EYENOR**°



## **ENR-02008-N-MPK**

표	Model No.	ENR-02008-N-MPK		
MODEL	Туре	8CH EMBEDDED NETWORK VIDEO RECORDER		
MONITORING	Preview Capability	1x8MP/1x6MP/1x5MP/2x4MP/2x3MP/4x1080P/8x720P/10x4CIF		
	Synchronous Playback	1x8MP/1x6MP/1x5MP/2x4MP/2x3MP/4x1080P/8x720P		
	Live View Functions	Screen matrix, Stream type, System alarm, Snapshot, Record, Talkback, Volume adjustment, Full screen, Digital zoom		
	Playback Functions	Sync playback, Play, Pause, Stop, Fast play, Slow play, Full Screen, Backup selection, Snapshot, Clip management, Screen matrix, Stream type		
Ξ	Corridor Mode	Supported		
8	Backup Mode	USB, Network, SATA burner		
	Export Picture Format	JPG		
	Export Video Format	MP4, SDV, AVI		
	Download from Edge storage	MP4, SDV, AVI		
INTERFACE	Protocols	TCP/IP, UDP, IPV4, IPV6, ICMP, HTTP, HTTPS, DHCP, DNS, DDNS, RTP, RTSP, RTCP, RTMP, FTP, NFS, PPPoE, NTP, UPnP, QoS, SMTP, IGMP, Multicast, ARP, SNMP, SSL, Telnet		
	Compatibility	ONVIF Profile (S, G, T)		
	Network	1xRJ45 (10/100/1000 Mbps) Self Adaptive Ethernet Port		
	Serial Interface	N/A		
	USB Interface	2xUSB 2.0		
	Alarm Interface	4 Input & 1 Output		
	PoE Interface	8xRJ45 (10/100 Mbps) Self Adaptive Ethernet Port		
PoE	Power per PoE Port	30 W		
ڇ	Max. Current per PoE Port	600 mA		
ı.	Alarm Management	Input & Output event, Alarm I/O error, Illegal access, IP Conflict, MAC Conflict, Network Interrupt, PoE overload, Hard disk full, No hard disk, Hard disk R/W error, Hard disk overload, HDD SMART check error, Abnormal recording, Abnormal temperature, Motion detection, Tampering (Masking), Smart detection, Video loss		
SMART	Behavior Detection	Intrusion (Perimeter), Crossline (Tripwire), Double Crossline (Double Tripwire)		
SM	Analytics	Loitering, Running, Abandoned object (Object Left), Missing object (Object Lost), Parking, Face Detection (Capture), People Counting, Crowd Detection, On Duty Detection, Abnormal Video & Audio Detection, Auto Tracking, Heatmap  **Compatible with analytic supported cameras		
	SATA	2 SATA Interfaces		
STORAGE	Capacity	Up to 10 TB for each HDD		
Z .	Array Type	N/A		
STC	e-SATA	N/A		
	ANR	Supported		
	Main Processor	Dual Core Embedded Processor		
	Operating System	Embedded Linux		
	User Permission	32 with multiple privilege level		
	Web Client	EyeConnect		
	Web Language	14		
₹	Power Redundant Power	100~240V AC, 50~60 Hz N/A		
GENERAL	Power Consumption (without HDD)	N/A ≤25 W		
떙	Working Environment	-10 °C ~ 55 °C		
	Humidity	10% ~ 90% RH		
	Chassis	10 % ~ 90 % KIT		
	Dimension	47.5×277×440 mm		
	Net Weight	2.9 kg		
	The Weight			

# 8CH EMBEDDED NETWORK VIDEO RECORDER **EYENOR**°



## **ENR-02008-N-MPK**





### ORDERING INFORMATION

Part Number	Description	Standard Quantity
ENR-02008-N-MPK	8Ch Embedded Network Video Recorder with 2 HDD Bays, Supports 8# PoE Ports, 4K Cameras, HDMI, VGA and ONVIF	1

### **PACKING INFORMATION**

Part Number	Packing Mode	Gross weight(Kg)	Dimension(mm)
ENR-02008-N-MPK	Carton Box	4.25	47.5×277×440