


# 4CH MOBILE NVR



**ENR-21004-N-RK**

## FEATURES

- \_\_\_\_\_ H.265 Compression
- \_\_\_\_\_ 8-36V Wide Voltage
- \_\_\_\_\_ Real Time Monitoring
- \_\_\_\_\_ SD Card Storage up to 128 GB
- \_\_\_\_\_ Support GPS, Wi-Fi and 4G
- \_\_\_\_\_ NTP Supported



## SPECIFICATION

MODEL	Model No.	ENR-21004-N-RK
	Type	4CH MOBILE NVR
VIDEO & AUDIO	Image Resolution	4x1080P (1920x1080)
	Video Compression	H.265, H.264, MPEG4, MJPEG
	Streams	Dual Stream Independently Configurable
	Video Input	4Ch IPC 1080P Input
	VGA Output	1Ch, support 1920x1080, 1280x720, 1024x768
	CVBS Output	1Ch Aviation Output PAL/NTSC, 1.0Vp-p, 75Ω
	Video display	Single / Four
	Video Standard	PAL / NTSC : 25/30fps
	System Resource	PAL / NTSC : 100/120fps
	Playback Resolution	1- 4CH x 1080p
	Image Quality	1-8 Levels Adjustable
	Video Bit-Rate	192 kbps ~ 8 Mbps (per channel)
	Video Space Requirement	85 ~ 1800M Byte/hour
	Record Format	Synchronized Video & Audio
Audio compression	G.711A / G.711U	
Audio Bit-Rate	4K Byte/s (per channel)	
Recording	Modes: Normal, Schedule based, Alarm, Motion detection, Video loss, Camera Cover, Vehicle Speed Event Based : Pre and Post Recording. Up to 1 ~330 s Configurable	

# 4CH MOBILE NVR



## ENR-21004-N-RK

MODEL	Model No.	ENR-21004-N-RK
	Type	4CH MOBILE NVR
INTERFACE	Compatibility	ONVIF
	Network	1xRJ45 (10M/100M/1000M) Self Adaptive Ethernet Port(Optional)
	Security	AES Encryption, Password Protection
	Serial Interface	3xRS232, 2xRS485 (Optional)
	Wi-Fi	Built-in Wi-Fi module 2.4GHz/5.8GHz (IEEE802.11n/g/b)
	USB	2xUSB 2.0
	GPS	Supported
	SIM Slot	1 x 3G/4G
	Vehicle Data Collect	1Ch Pulse Speed Detection
	Intercom	1xMIC Input for Two Way Communication (Optional)
	Analog Input	2Ch
	G-Sensor	Built-in G-Sensor
	CANBUS	Optional 2xCANBUS modules
	Audio I/O	4/1
	Alarm I/O	12/3
	Edge Storage	Micro SD card slot, up to 128GB
HDD	2 x 2.5" SATA HDD(7mm thick), max 4TB	
GENERAL	OS	LINUX
	Operation Interface	Graphical Menu Operation Interface (OSD Menu)
	Notifications via Mail / SMS	Vehicle Speed, Vehicle Acceleration, Alarm Triggered, Video Loss, Camera Tamper, SSD Error
	Watermark	Supported
	Power	DC8-36V
	Max. Power Consumption	≤12W
	Working Temperature	-40 °C ~70 °C
	Working Humidity	≤80%
	Dimensions	235x190x80 mm
	Weight	3.0 kg

### ORDERING INFORMATION

Part Number	Description	Standard Quantity
ENR-21004-N-RK	4Ch Mobile NVR with 2 HDD Bay, 1 SD Card Slot, GPS, Wi-Fi and 4G Support	1

### PACKING INFORMATION

Part Number	Packing Mode	Gross weight(Kg)	Dimension(mm)
ENR-21004-N-RK	Carton Box	-	-