



#### **FEATURES**

Supports face statistics in list or graphics

Supports managing up to 64 people counting cameras in one zone and displaying real-time statistics

Supports people counting statistics in list or graphics

Add device via P2P

Live view with audio and remote playback through P2P

Switch P2P server region

#### **SPECIFICATION**

핃	Model No.	ENS-EYECONNECT		
MODEL	Туре	Eyenor Video Management Software		
	Supported Devices	IPC, NVR, XVR, PTZ etc.		
	Max Connected	200 IP devices or 512 channels		
	Device Management	Add/delete/edit user and configure user authority, Set period of validity		
	System Framework	Common functions and basic functions		
		Drag to add new function icon or remove it		
		Drag to change function icon order		
	Login	Create password when first start the software		
		Support forgot password by protection questions		
		Auto login, remember password		
		Support switching languages in login interface		
		Auto search devices within same LAN, supports batch and one-key addition		
		Support manual addition by IP, DDNS, EasyDDNS, P2P (Only for Windows version)		
	Davisa Managanant	Support group management		
	Device Management	Support acquiring device channel name or sync channel name to devices		
ESS		Support jumping to device IE interfaces in default browser		
XPR		Support export and import of device and group organization list		
EYECONNECT SMART CLIENT EXPRESS	Preview	Support device list and device online status		
E		Support one-key to connect/disconnect all channels		
ART		Support 1/2/3/4/1-5/1-7/9/10/13/16/17/25/36/49/64 window division mode and customization of display split		
. SM,		Support to enable/disable audio and two-way audio		
		Support capture and one-key to capture all channels		
NO		Support to switch main and sub stream, set video parameters		
YEC		Support record and one-key to record all channels		
ш		Support PTZ control, focus, aperture, preset, light/wiper control		
		Support saving view, view rotating and group switch		
		Support face capture and display body temperature info during preview		
		Support face recognition and display comparison result		
		Support device list and device online status		
	Playback	Playback control, play/pause/fast forward/slow forward/step forward		
		Support 1/2/3/4 window division mode		
		Support capture and one-key to capture all channels		
		Support to enable/disable audio		
		Search video by calendar, date, storage location, stream type, etc.		
		Download video clip by file or by time		
	Operation Logs	Query operation logs by time, type, user, etc.		
		Export log information		







## **EYENOR VIDEO MANAGEMENT SOFTWARE**





# **ENS-EYECONNECT** (For windows)

### **SPECIFICATION**

PEL	Model No.	ENS-EYECONNECT		
<u>8</u>	Туре	Eyenor Video Management Software		
DATA STATISTICS SMART CLIENT EXPRESS MODEL	Intelligent Search	Retrieve face pictures by time, gender, age, mask, glasses, body temperature		
		Result can be displayed in list or figure		
		Check detailed picture or video		
		Export data		
	Face Statistics	Show face data statistics in list or graphics according to different filter		
	Visitor Flow Statistic	Manage up to 64 people counting camera in one zone and set configuration of people counting rule		
		Preview of people counting camera		
		Display peak number, current number and line chart in real time		
		Support to set time duration of people counting, people capacity alarm, rapidly increased number alarm and number of people stay		
		Show reported statistic in list or graphics according to different filter		
		Set capture and download file path		
		Automatic login		
		Data backup/recover/clear up/re index (re index face capture and record)		
	Common Settings	Change language and software skin		
		English		
Z		Set save time of log and alarm log		
SYSTEM CONFIGURATION	Video	Set stream switch by automatically or manually		
3UR		Set play strategy, good fluency or minimum delay		
NFI		Hardware decoding available for Windows version		
00		Set download format, SDV, AVI and MP4 are supported		
STEN	Alarm Grade	Set alarm grade		
S	Storage Management	Set recoding package time, format, stream type		
		Set space strategy, storage location		
	Intelligent Application	Enable intelligent application to receive face capture pictures and face recognition results		
		Set face picture save duration by day		
		Check deletion strategy to set visitor flow statistic save duration by month		
	P2P Setting	Set P2P server region		
ALARM	Real Time Alarm	Real time alarm in Alarm Management, quick to play alarm video or real time video		
		Support alarm filter by alarm grade		
		Operator can handle and input comment to real time alarm		
		Turn on/off alarm audio of software		
	History Alarm	Query history alarm by time, source, status, user		
		Support alarm filter by alarm grade		
		Operator can handle and input comment to history alarm		



# **ENS-EYECONNECT** (For windows)

CONNECTION PERFORMANCE				
Device Type	Network	Channels Number		
Eyenor Device	LAN	512		
Eyenor P2P Devices	WAN	512		

EXPORT PERFORMANCE OF FACE PICTURE							
Data	Windows	Mac Mini	MacBook	iMac			
1 Day Per Channel	3s	<3s	<3s	<3s			
1 Week Per Channel	10s	11s	7s	8s			
1 Month Per Channel	48s	1′20″	19s	30s			
3 Month Per Channel	30′7″	5′59″	1′27″	1′55″			
91W Face Pictures	4h7min	40min	1h2min	1h19min			

RECOMMENDED SYSTEM REQUIREMENT				
OS	Windows7, window10, Mac OS			
CPU	i5-8Generation			
Memory	4G			
HDD	512G			
Network Card	100/1000M Self Adaptive			
GPU	GTX1050 4G			
Display	1920x1080			

 $<sup>\</sup>ensuremath{^{**}}$  Software specifications are subject to change without any prior notification.



