
# 1 Pair 24 AWG Overall Braid Shielded Paired Cable RS 485

**POLYNOR** 

The Overall braid shielded paired cable from NORDEN is suitable to use with in Audio, Control and Instrumentation purpose. The cable is constructed with PP or PE Insulation, 100% Aluminium Foil-Polyester Tape Overall Shielded with Tinned braid Coverage. This Cable is protected by PVC or LSZH outer Jacket.



# **CABLE CONSTRUCTION**

ConductorShieldingBraid Shield CoverageOuter JacketTinned CopperAluminium Foil -<br/>Polyester Tape90% Tinned CopperPVC / LSZH


InsulationFoil CoverageDrain WireJacket ColorPE/PP100%Tinned CopperGrey

## PHYSICAL CHARACTERISTICS

Characteristic	Value	
No. of Pair	1	
Conductor Size	24 AWG 7 x 32	
Insulation Thickness	0.40 mm	
Insulation Diameter	1.72 mm	
Drain Wire Size	24 AWG 7 x 32	
Jacket Thickness	0.70 mm	
Jacket Diameter	er 4.5 mm	
Max. Recommended Pulling Tension	ion 238 N	
Min. Bending Radius Minor Axis	44.45 mm	
Operating Temperature	-30℃ to +60℃	

### **ELECTRICAL CHARACTERISTICS**

Characteristic	Unit	Value
Nom. Characteristic Impedance	Ω	120.0
Nom. Capacitance Cond. to Cond.	pF/m	42.2
Max. Conductor DCR	Ω/km	77.7
Nom. Capacitance Cond. to Cond. & Shield	pF/m	75.67
Max. Recommended Current @ 25°C	Amps	2.75
Max. Operating Voltage UL	V/min	300



# 🚽 😭 🗂 Building & Industrial Cables - Version 1.0

# 1 Pair 24 AWG Overall Braid Shielded Paired Cable RS 485

# **POLYNOR**

## **MECHANICAL CHARACTERISTICS**

Characteristic	Value	
Test Material	PVC & LSZH	
Before Tensile Strength (Mpa)	ength (Mpa) ≥13.8	
Aging Elongation (%)	≥100	
After Tensile Strength (Mpa)	gth (Mpa) ≥10.35	
Aging Elongation (%)	on [%] ≥75	
Cold Bend (-20±°C x 4 hrs)	No Crack	

### **INSULATION COLOUR CODE**

Individual Pair	Colour
Pair 1	White/Blue

# ORDERING INFORMATION

Part Number	Description	Net Weight Kg/km
78-4501241	1 Pair 24 AWG Overall Braid Shielded Paired Cable RS485 PP Insulation	31
78-3501241	1 Pair 24 AWG Overall Braid Shielded Paired Cable RS485 PE Insulation	31
78-3501242	1 Pair 24 AWG Overall Braid Shielded Paired Cable RS485 PE Insulation, LSZH Jacket	32.5