

FIBRE PATCH CORD

They comprise two tight buffer fibres housed within a common outer jacket in OM1, OM2, OM3, OM4, OS1, OS2 multi-mode and single mode variants. Both ends are terminated with a high performance hybrid type connector comprising of a Uniboot LC, SC, connector in duplex. These are typically not ruggedized, depending on the application and a spring loaded electrical contact housed within LSHF plastic shell possible, making them suitable for internal use.



COMPLIANCE

Telcordia (formerly Bellcore) GR-326-CORE Generic requirements for Single mode optical connectors and Jumper assemblies.

IEC 874-1 Generic specification for fibre optic connectors and cables

ANSI/TIA-568-C.3, ISO/IEC 11801 2nd Ed., CENELEC EN 50173, UL94V-0

Cable flame resistant rate: OFNR or IEC60332-3 standard

KEY FEATURES

Uniboot LC, SC, connectors

Position A/Position B markings

100% factory transmission tested per ANSI/TIA-568-C.3

Slim-profile boots with durable flexible cable strain relief

Available in 0.9mm, 1.6mm, 2.0mm , 3.0mm sizes

MECHANICAL & ENVIRONMENTAL CHARACTERISTICS

Range of Mode	Single or Multimode
Cable Type	Uniboot Duplex Zipcord
Connector Style	Uniboot LC, SC
Polish or Ferrule Interface Type	PC, UPC, APC
Cable Diameter	0.9mm, 1.6mm, 2.0mm, 3.0mm
Lengths	Standard & Custom Lengths
Strength Member	Aramid Yarn
Outer Jacket	PVC or LSZH
Cable Assembly Length (<15 meter Tolerance)	-0/+100mm
Cable Assembly Length (>15 meter Tolerance)	-0/+10%
Jacket Colour (Multimode: OM1 & OM2)	Orange
Jacket Colour (Multimode: OM3 & OM4)	Aqua
Jacket Colour (Single Mode: OS1 & OS2)	Yellow
Durability	500 cycles(0.2 dB max increase), 1000mate/demate cycles
Operating Temp.	-20 °C to +70°C/+85°c (armoured)
Storage Temp.	-40 °C to +85 °C
Ferrule Concentricity	< 1µm, Other Ferrule Concentricity < 1µm
Humidity (FOTP-5)	90-95% at 40°C
Strength of Coupling Mechanism (FOTP-185)	33 N at 0° for 5 sec
Cable Retention (FOTP-6)	50 N at 0° for 5 sec.
Twist (FOTP-36)	15 N at 0° 5 turns, 10 cycles
Flex (FOTP-1)	0.5 Kg at 25 cm, +90° to -90°, 100 cycles

FIBRE PATCH CORD

OPTICAL CHARACTERISTICS

Fibre Type	Max. Attenuation (dB/km)				Min. Overfill Launch Bandwidth (Mhz•km)		Min. Gigabit Ethernet Link Distance (m)		
	850nm	1300nm	1310nm	1550nm	850nm	1300nm	Gigabit		10Gigabit
							850nm	1300nm	850nm
OM1 62.5/125	≤2.7	≤0.6	-	-	≥200	≥600	275	550	-
OM2 50/125	≤2.5	≤0.7	-	-	≥500	≥500	550	550	-
OM3 50/125	≤2.3	≤0.6	-	-	≥1500	≥500	1000	600	300
OM4 50/125	≤2.3	≤0.6	-	-	≥3500	≥500	1000	600	550
OS1 9/125 [G652.B]	-	-	≤0.34	≤0.20	-	-	-	-	-
OS2 9/125 [G652.D]	-	-	≤0.34	≤0.24	-	-	-	-	-
OS2 9/12 [G5657.A1]	-	-	≤0.35	≤0.21	-	-	-	-	-
OS2 9/125 [G657.A2]	-	-	≤0.35	≤0.21	-	-	-	-	-
OS2 9/125 [G655]	-	-	-	≤0.22	-	-	-	-	-

OPTICAL PERFORMANCE DATA

Item	Single mode			Multimode		
	PC	UPC	APC	62.5/125	50/125	50/125 10G
Insert. Loss/connector (single Fibre)	0.2dB Max. (0.15dB typ.)			0.3dB Max. (0.25dB typ.)		
Return Loss	≥ 45 dB	≥ 50 dB	≥ 60 dB	N.A		
Insert. Loss/MTRJ Connector	0.5dB Max. (0.45dB typ.)			0.5dB Max. (0.45dB typ.)		
Pull strength	≥98N	≥98N	≥98N	≥98N		

TERMINATION SPECIFICATIONS

Geometric Specifications	
Radius of Curvature	7-25 mm
Apex Offset	0-50 um
Radial Fibre Height	-50 to +50 nm
Angular Offset	<0.3 degrees
Fibre Roughness	0-25 nm
Ferrule Roughness	0-50 nm
End Face Defects	
Fibre Core	0 nm ²
Mode field diameter	0 nm ²
Ferrule contact zone	0 nm ²
Testing & Inspection	100%
Epoxy	
Temperature Coeff .Tg	120
Curing Method	Out Gassed
Residual Epoxy	No Visible Epoxy Ring
Configuration Control	
Serialization	Each Cable is Serialized

FIBRE PATCH CORD

UNIBOOT LC - LC FIBRE PATCH CORD

Uniboot LC - LC Singlemode Patch Cord	OS2 (9/125) G652.D	OS2 (9/125) G5657.A1
Uniboot LC/PC - LC/PC 1m Duplex PVC	332-130S2U1U1001	332-137A1U1U1001
Uniboot LC/PC - LC/PC 2m Duplex PVC	332-130S2U1U1002	332-137A1U1U1002
Uniboot LC/PC - LC/PC 3m Duplex PVC	332-130S2U1U1003	332-137A1U1U1003
Uniboot LC/PC - LC/PC 5m Duplex PVC	332-130S2U1U1005	332-137A1U1U1005
Uniboot LC/PC - LC/PC 10m Duplex PVC	332-130S2U1U1010	332-137A1U1U1010
Uniboot LC/PC - LC/PC 15m Duplex PVC	332-130S2U1U1015	332-137A1U1U1015
Uniboot LC/PC - LC/PC 20m Duplex PVC	332-130S2U1U1020	332-137A1U1U1020
Uniboot LC/PC - LC/PC 1m Duplex LSZH	332-230S2U1U1001	332-237A1U1U1001
Uniboot LC/PC - LC/PC 2m Duplex LSZH	332-230S2U1U1002	332-237A1U1U1002
Uniboot LC/PC - LC/PC 3m Duplex LSZH	332-230S2U1U1003	332-237A1U1U1003
Uniboot LC/PC - LC/PC 5m Duplex LSZH	332-230S2U1U1005	332-237A1U1U1005
Uniboot LC/PC - LC/PC 10m Duplex LSZH	332-230S2U1U1010	332-237A1U1U1010

Uniboot LC - LC Multimode Patch Cord	OM1 (62.5/125)	OM2 (50/125)	OM3 (50/125)	OM4 (50/125)
Uniboot LC/PC - LC/PC 1m Duplex PVC	332-130M1U1U1001	332-130M2U1U1001	332-130M3U1U1001	332-130M4U1U1001
Uniboot LC/PC - LC/PC 2m Duplex PVC	332-130M1U1U1002	332-130M2U1U1002	332-130M3U1U1002	332-130M4U1U1002
Uniboot LC/PC - LC/PC 3m Duplex PVC	332-130M1U1U1003	332-130M2U1U1003	332-130M3U1U1003	332-130M4U1U1003
Uniboot LC/PC - LC/PC 5m Duplex PVC	332-130M1U1U1005	332-130M2U1U1005	332-130M3U1U1005	332-130M4U1U1005
Uniboot LC/PC - LC/PC 10m Duplex PVC	332-130M1U1U1010	332-130M2U1U1010	332-130M3U1U1010	332-130M4U1U1010
Uniboot LC/PC - LC/PC 15m Duplex PVC	332-130M1U1U1015	332-130M2U1U1015	332-130M3U1U1015	332-130M4U1U1015
Uniboot LC/PC - LC/PC 20m Duplex PVC	332-130M1U1U1020	332-130M2U1U1020	332-130M3U1U1020	332-130M4U1U1020
Uniboot LC/PC - LC/PC 1m Duplex LSZH	332-230M1U1U1001	332-230M2U1U1001	332-230M3U1U1001	332-230M4U1U1001
Uniboot LC/PC - LC/PC 2m Duplex LSZH	332-230M1U1U1002	332-230M2U1U1002	332-230M3U1U1002	332-230M4U1U1002
Uniboot LC/PC - LC/PC 3m Duplex LSZH	332-230M1U1U1003	332-230M2U1U1003	332-230M3U1U1003	332-230M4U1U1003
Uniboot LC/PC - LC/PC 5m Duplex LSZH	332-230M1U1U1005	332-230M2U1U1005	332-230M3U1U1005	332-230M4U1U1005
Uniboot LC/PC - LC/PC 10m Duplex LSZH	332-230M1U1U1010	332-230M2U1U1010	332-230M3U1U1010	332-230M4U1U1010

ORDERING GUIDE

Patch Cord	Outer Jacket	Cable Dia.	Fibre Type	Connector	Polish	Connector	Polish	Length (mtr)
331: Simplex 332: Duplex	1: PVC 2: LSZH 3: PE 4: Arm./PVC 5: Arm./LSZH	1:0.9mm 2:1.6mm 3:2.0mm 4:3.0mm	OM1 OM2 OM3 OM4 OM5 OS1 OS2 7A1 = G657.A1 7A2 = G657.A2 7B2 = G657.B2 7B3 = G657.B3 500 = G655	S: SC T: ST F: FC L: LC U: Uniboot LC M: MTRJ E: E2000	1: PC 2: UPC 3: APC 4: APC 8°	S: SC T: ST F: FC L: LC U: Uniboot LC M: MTRJ E: E2000	1: PC 2: UPC 3: APC 4: APC 8°	XXX