FLOOR STANDING EXTERNAL NETWORK ENCLOSURE IP55




The Easycab range of floor standing cabinet IP55 designed for external telecommunication purpose. The smart design and professional engineering provides easy installation and maintenance. It is comply with ANSI/EIA RS-310-D, IEC 297-2, DIN 41491, PART 1, DIN 41497, PART 7, GB/T3047.2-92, ETSI standards.


FEATURES


- Intelligent design ensures easy installation
- Protected against dust limited ingress and protected against low-pressure jets of water from all directions
- LED bulbs are installed to level up the visibility inside the cabinets
- Protection grade IP55, effectively prevents rain leakage
- Comes with the installed Smoke Transducer to detect the smoke
- Door access control keep a check on accessibility at the entrances /door


Material	Galvanized sheet	
Deg. of Protection	IP55	
Surface finish	Degreasing, Phosphoric, Powder coated	
Color	RAL7035	
Loading capacity	900 Kg	
Material thickness	Single layer Frame & Top 1.5mm, mounting profile 2.0mm, Plinth 1.5mm	

DRAWING









FLOOR STANDING EXTERNAL NETWORK ENCLOSURE IP55

ORDERING INFORMATION

Part Number	Number Description		Dimension(mm)	
700X700				
13K6-237720X	23U 700x700 Single Section with Smoke Detector, Door access control IP 55 Network Enclosure	23U	700X700X1300	

PACKING INFORMATION

Part Number	Packing Qty.	Packing Mode	N.W (kg)	G.W (kg)	Dimension (mm)
13K6-237720X	1 x 1	Carton Box	95.0	120.0	800X800X1500