

6.5" Fireproof Ceiling Speaker 6W



DESCRIPTION

NVS-10460006CS is a ceiling speaker designed for voice evacuation systems. This have a built in 100V Transformer so transmission is realized in a high-voltage, low-current mode. This will make possible of longer distance transmission and parallel connection of multiple loudspeakers. It is made of high-class steel and fixed by stamping. This ensures long-term durability, and will never be out of shape. Equipped with fire dome which is hard to burn during fire situation. It is an ideal choice for industrial and commercial applications like in hotel, school, office and factory where background music and paging is required.

FEATURES

- Crisp and clear Sound
- Comply with EN54-24 requirements
- Equipped with fire-proof dome
- Aluminum grille, stainless and durable
- High-class steel and form by stamping
- Clip type flush mount design for easy installation

Specifications

Model	NVS-10460006CS
Rated Power	6W
Driver Unit	6.5"×1
Frequency Response	180Hz~16kHz
Input Voltage/Impedance	70V/100V
Sensitivity (1m,1w)	90dB±2dB
Maximum SPL (1m)	97dB±2dB
Weight	1.04kg
Dimension	Ø200×98mm

ORDERING INFORMATION

Part Number	Description	Standard Quantity
NVS-10460006CS	6.5" Fireproof Ceiling Speaker 6W	01