

Wall Mount Audio Intercom



DESCRIPTION

NVS-IP20024IC is a SIP intercom terminal which developed on the technical basis of VOIP phone and the needs of users. The voice transmission is under the standard IP/RTP protocol, which can be perfectly compatible with all the mainstream IP PBX/ soft exchange /IMS platforms based on SIP, which brings convenience for system configuration. The housing of the product is made of high strength aluminum alloy material, and the bottom shell is made of iron. This product is waterproof and dustproof, with IP54 Protection. The housing is firmly fixed by hex screws, which can effectively prevent dust and reduce damage caused by the impact of hard objects. It is a trust-worthy intercom product for users.

FEATURES

- ⦿ Support POE power supply
- ⦿ Comply IP54
- ⦿ Editable call button
- ⦿ External active speaker output interface
- ⦿ 2 SIP lines
- ⦿ Wall-mounted installation

Specifications

Model	NVS-IP20024IC
Audio Amplifier	2.4W
Volume Control	Adjustable
Full Duplex Hands-free	Support (AEC)
Communication Protocol	SIP 2.0(RFC-3261)
Speaker	1 (XH2.54 pin)
External Speaker	1 (3.5mm pin)
Short Circuit Input	2 (3.5mm pin)
Short Circuit Output	2 (3.5mm pin)
Line Input	1 (3.5mm pin)
Line Output	2 (3.5mm pin)
Working Voltage	POE power supply or 12V / 1A DC
Working Temperature	-20°C to 70°C
Dimension (mm)	190×115×45
Weight	0.5KG

NVS-IP20024IC



Wall Mount Audio Intercom

ORDERING INFORMATION

Part Number	Description	Standard Quantity
NVS-IP20024IC	Wall Mount Audio Intercom	01

PACKING INFORMATION

Part Number	Packing Mode	Gross weight(Kg)	Dimension
NVS-IP20024IC	Carton Box	0.9KG	268×173×73