

UTP PUNCH DOWN KEYSTONE JACK

UTP keystone jack with shutter exceed TIA/EIA and ISO component and channel performance, can be used in unloaded patch panels, faceplates and shutters, in a variety of colour options. These Jacks are designed to reduce the Insertion loss & Alien cross talk in order to provide maximum flexibility and high performance and are available in a 180° orientation with a dual termination block which will allow the installer to terminate with either a 110 or Krone insertion tool. This supports T568 A & B wiring & easy installation. The jack is manufactured with an integral cable strain relief.



COMPLIANCE

IEEE 802.af, IEEE 802.3at for PoE applications.
ANSI/TIA-568.2-D, ISO/IEC-11801, EN50173-2

DESIGN & MATERIALS

Colour	Black or Others Available Upon Request
Size	26.2 mm X 17 mm X 35.1 mm
Angle	180 Degree
Temperature	-40 °C to +70 °C (Storage), -10 °C to +65 °C (Operation)
Housing Material	High Impact, Flame-Retardant Plastic Compound, UL 94 V-0
IDC Type	Dual (110 Or Krone) Type
IDC Wire Gauge	22-26 AWG, Solid or Stranded
Colour Coding	As Per 568 A/B Standard

STANDARDS

Flammability Rating	UL 94 V-0
Safety Rating	UL 1863

ELECTRICAL DATA

Current Rating	1.5 A
Insulation Resistance Ω min 100 V dc	500 M
Voltage Rating	230 V rms max.
Dielectric Voltage	1000 V dc or ac, 60 Hz for 1 min (Contact-Contact)

ORDERING INFORMATION

Part Number	Description
122-21P181X	Category 5e UTP Keystone Jack Shuttered 180D
122-31P180X	Category 6 UTP Keystone Jack Without Shutter 180D
122-31P181X	Category 6 UTP Keystone Jack Shuttered 180D
122-41P180X	Category 6a UTP Keystone Jack Without Shutter 180D

X: BK(Black), BL(Blue), GN(Green), GY(Gray), RD(Red), WH(White), YL(Yellow)

PACKING INFORMATION

Part Number	Packing Qty.	Packing Mode	N.W (kg)	G.W (kg)	Dimension (mm)
122-21P181X	96 x 20 x 1	Carton Box	16.0	20.0	620 x 420 x 430
122-31P180X	96 x 20 x 1	Carton Box	15.5	19.5	620 x 420 x 430
122-31P181X	96 x 20 x 1	Carton Box	16.6	20.0	620 x 420 x 430
122-41P180X	96 x 20 x 1	Carton Box	15.5	19.5	620 x 420 x 430