

2 Zone Fireman Microphone



DESCRIPTION

The NVS-5013FM05EV is a wall-mounted microphone that works with the NVS-50120482EV, the 2 Zones Voice Evacuation System Host and supports real-time monitoring. It has a maximum audio transmission distance of 500 meters and redundant wiring. This device supports the remote control of the Evacuation Host system and it can be operated from anywhere within the network. The device have one-key alarm function and two editable alarm voices for broadcasting customized messages.

FEATURES

- ⦿ Fireman emergency microphone
- ⦿ Support 500 meters audio transmission
- ⦿ Support redundant wiring
- ⦿ Support real-time monitoring of microphone
- ⦿ LED light display to indicate the connection status
- ⦿ One-key alarm function and two editable alarm voices
- ⦿ With operation permission control

Specifications	
Model	NVS-5013FM05EV
Sensitivity	5mv (±1mv)
Signal to Noise Ratio	≥70dB
Frequency Response	100Hz-10KHz(±3dB)
Working Voltage	DC24V (connect to the NVS-50120482EV host with network cable)
Dimension	300×240×100mm
Weight	3.2Kg

ORDERING INFORMATION

Part Number	Description	Standard Quantity
NVS-5013FM05EV	2 Zone Fireman Microphone	01