### NVS-20210451AM

## **PA Power Amplifier 450W**





### DESCRIPTION

The NVS-20210451AM is a public address Power Amplifier with rack mount design in 2U type. Each channel features both balanced and unbalanced line inputs. The balanced line output feeds another power amplifier, ensuring that the signal is transmitted with less noise and over a longer distance. When selecting different speaker matching, 70V, 100V, and  $4-16\Omega$  speaker outputs are convenient for installation. There is also a master volume control. Clip, short circuit, high temperature, and overload protection are all included. Power, signal, clip, protection, and temperature are all indicated.

#### **FEATURES**

- Rack mount amplifier in 2U height
- Isolated transformer for human safety operation
- 5 LED indicator for status display
- XLR socket and 6.35mm jack for additional mixer or amplifier link
- ⊙ Indications for power, signal, clip, protection and temp
- ⊙ Reliable protection from overheat, overload, clip & short circuit
- Excellent device of radiator cooling fan ensures working effectively


Specifications		
Model	NVS-20210451AM	
Rated Power	450W	
Frequency Response	50Hz ~15kHz (±3dB)	
Input Sensitivity(1m,1w)	OdBu	
Total Harmonic Distortion	<0.3% into 4Ω/1kHz	
Signal to Noise Ratio	> 80dB	
Input CMRR	>90dB	
Slew Rate	>15V/microsecond	
Damping Factor	200:1	
Rated output voltage	70V/100V/4-16Ω	
Power Consumption	700W	
Power Supply	AC220~240V / 50~60Hz	
Weight	17Kg	
Dimension	483x380x88mm	

## NVS-20210451AM




# **PA Power Amplifier 450W**

### **FRONT PANEL**



### **REAR PANEL**



### **ORDERING INFORMATION**

Part Number	Description	Standard Quantity
NVS-20210451AM	PA Power Amplifier 450W	01