

IEC C13 PDU WITH C14/INDUSTRIAL 60309 PLUG



NORDEN Power Distribution Units are designed and manufactured in a modularized way exclusively for cabinets. The product is equipped with supply socket modules meeting different systems and standards in the world. The series products can be produced accordingly to customers' special requirements.

COMPLIANCE

EMC & safety:-EN 55022 Class A,EN 55024,EN 61000-3-2,
EN 61000-3-3,FCC Part 15 Class A,
ICES-003,PSE, VCCI Class A,VDE
Environmental: RoHS, REACH: Contains No SVHCs
Socket/Outlet Standard: IEC C13

DESIGN & MATERIALS

| | |
|----------------------------|------------------------------------------------------------------|
| Material of Construction | PC/ABS alloy, High Impact flame retardant thermoplastic –UL94-V0 |
| Shell Material & Colour | Aluminium, black |
| Outlet Qty. | 10 way |
| Plug Type | Industrial Plug / C14 Male Plug |
| Power Input Style | Left-end single input style |
| Bracket Installation Style | Frontal Installation Style |
| Control function | Switch |
| Commando Plug protection | IP44 |
| Lead length | 3m,4m,5m (other cable lengths available on request) |

ELECTRICAL & ENVIRONMENTAL DATA

| | |
|-----------------------------------|-----------------|
| Current Rating | 10A, 16A 250VAC |
| Maximum load current available in | 10A or 16A |
| Input frequency | 50 or 60 Hz |
| Maximum load capacity | 4KW |
| Operating Environment | -5 °C to +45 °C |
| Operating Relative Humidity | 5 – 95 % |
| Operating Elevation | 0-3000 meters |
| Storage Temperature | -25°C to +65 °C |
| Storage Elevation | 0-15000 meters |

ORDERING INFORMATION

| Part Number | Description |
|------------------|-----------------------------------------------------------------------------------------------|
| 17FM-910A10N005X | 10 Way PDU, C13 Socket,10Amp, C14 Plug Male,4 Meter Cable Length 19" installation |
| 17FM-210A10N005X | 10 Way PDU, C13 Socket, 16Amp Industrial IP44 plug Male,4 Meter Cable Length 19" Installation |