

# IP Based Remote Paging Mic with Video intercom



## DESCRIPTION

The NVS-IP100026PM is an IP based remote paging microphone with video intercom and has a professional modular console design. It is equipped with 10.2" digital TFT true color LCD display & capacitive touch screen (resolution: 1280×800). It is integrated with 13 mega-pixel HD digital camera for two-way video intercom with other video intercom terminals. It contains built-in 3W speaker and unidirectional condenser microphone for two-way hands-free intercom and audio monitoring. It has built-in intelligent face recognition chip which can realize local face recognition. It supports pre-recording and file broadcasting function then the audio files or recordings can be broadcasted to the specified terminal. It is equipped with 1×Relay Input and 1×Relay Output interface for external linkage with emergency button, infrared detector, smoke detector, alarm light or electronic door lock.

## FEATURES

- ⦿ Equipped with 10.2" (1280\*800) digital TFT true color display & capacitive touch screen
- ⦿ Integrated 13 mega-pixel HD digital camera
- ⦿ Built-in 3W speaker and unidirectional condenser microphone
- ⦿ Equipped with detachable gooseneck microphone rod
- ⦿ Supports paging broadcasting to all zones, part zones or specific speaker
- ⦿ Provides three different calling modes for options: Dial Calling, Bookmarks Calling, Map Calling
- ⦿ Built-in intelligent face recognition chip
- ⦿ Able to check the network state
- ⦿ Professional modular console design

## Specifications

Model	NVS-IP100026PM
Audio Format	MP2/MP3/PCM/ADPCM
Audio sampling rate	8kHz ~ 48kHz
Transmission bit rate	8kbps ~ 320kbps
Built-in Speaker	3W, 4Ω
Signal to Noise Ratio	>85dB

## IP Based Remote Paging Mic with Video intercom

Frequency Response	25Hz ~ 20kHz
Built-in Camera	1/2.9", CMOS
Built-in Camera Resolution	13 Million Pixels
Built-in Camera Diafragma & Focal Length	F2.2, 3.69mm
Built-in Camera Horizontal/Vertical Viewing Angle	74.9°
Built-in Camera Frame Rate	25fps
Video Transmission bit Rate	512Kbps - 4Mbps
Display Screen	10.2 inch (1280*800), Capacitive Touch Screen
Product Material	Plastic
Protocol	TCP/IP, UDP, ARP, ICMP, IGMP, SIP, HTTP, RTP
Operating temperature	-10°C ~ +55°C
Operating Humidity	≤90% RH (Non Condensing)
Power supply	12V/3.3A, POE
Power Consumption	≤20W
Dimension	336x210x32.5mm
Weight	1.65KG

### ORDERING INFORMATION

Part Number	Description	Standard Quantity
NVS-IP100026PM,	IP Based Remote Paging Mic with Video intercom	01