

# Wall Mount Fireproof Projection Speaker 12W



## DESCRIPTION

The NVS-11320012PS is a wall mount fireproof projection speaker with plastic body made in ABS V0 type and the protection grid in aluminium. It comes with an aluminium mounting bracket, a waterproof cover, and IN-OUT cable glands for simple speaker daisy-chaining. It is mostly suitable for indoor installations.

## FEATURES

- ◉ Wide band bi-cone 5" speaker
- ◉ Protection grid in aluminium
- ◉ IP rating of IP54.
- ◉ Audio transformer for connection to 100V or 70V lines
- ◉ Thermal fuse for protection of the speaker line in case of overheating
- ◉ Dual IN-OUT ceramic connector
- ◉ 100V transformer

Specifications	
<b>Model</b>	<b>NVS-11320012PS</b>
Driver Size	5"x1
Rated Power	12W
Frequency Response [-10dB]	110Hz - 18kHz
Sensitivity (1m, 1W)	86.3 dB
Maximum SPL (1m)	97.2 dB
Power Tapping Options & Impedance	3W(3.33kΩ), 6W(1.66kΩ), 12W(833.3Ω)
Coverage angle [-6dB]	360° (500 Hz), 253.5° (1 kHz), 125.5° (2 kHz), 86.8° (4 kHz), 59.4° (8 kHz)
Weight	1.2 Kg
Dimensions	Ø140mm x 240mm
Aluminium bracket	Ø140mm x 152mm

**NVS-11320012PS**



# Wall Mount Fireproof Projection Speaker 12W

## ORDERING INFORMATION

Part Number	Description	Standard Quantity
NVS-11320012PS	Wall Mount Fireproof Projection Speaker 12W	01