NVS-30110006MP



High Fidelity Ceiling Mount Microphone



DESCRIPTION

The NVS-30110006MP is a high fidelity ceiling mount Microphone with professional interview microphone, refined design and circuit processing technology to make sound quality clear and natural. High speech intelligibility and a quick, stable response are two features of the sound pickup produced by the high-speed voice DSP processing unit and AEC technology. The signal transmission distance can reach 3000 metres when using the ultra-strong audio line transmission technology.

FEATURES

- Concealed anti-dropping structure
- Built-in AGC circuit
- Dual recording function
- Polarity reversal of power supply
- Lightning strike protection
- Self-checking functionality to automatically indicate the sound pickup's fault state
- ⊙ Integrated professional voice processing chip for connecting active speakers, PC, DVR, IP camera etc

Specifications		
Model	NVS-30110006MP	
Міс Туре	Gold Plated capacitor MIC	
Polar Pattern	Omni directional	
Frequency Response	20Hz~20KHz	
Sensitivity	-30dB	
Maximum SPL	110dB (@1KHz)	
Total Harmonic Distortion	0.6% (@1KHz 1VRMS)	
Sound Pickup Range	5-150 metre square	
Dynamic Range	90dB (@1KHz)	
Output Impedance	600Ω Unbalance	
Output Signal Amplitude (V)	1VRMS	
Material	Metal Shell	
Color	Silver	
Power Supply	DC 12V, 1A	



NVS-30110006MP High Fidelity Ceiling Mount Microphone



Working Temperature	-20°C~60°C
Weight	0.13Kg
Dimension	Ø80x24.6mm

ORDERING INFORMATION

Part Number	Description	Standard Quantity
NVS-30110006MP High Fidelity Ceiling Mount Microphone		01