

Coaxial Ceiling Speaker 20W



DESCRIPTION

The NVS-10350020CS is a Ceiling Speaker with built-in 70V/100V transformer. The transmission takes place in a high-voltage, low-current environment. Low-current mode allows for longer transmission distances and parallel connections of many loudspeakers. The built-in 6.5" speaker driver has a wide frequency response of 60-18,000Hz, and the multiple terminals of 10W and 20W may be used for a variety of events with different area sizes and background noises. It is made of high-quality engineering plastic, which assure a long-term durability and never out of shape and the will not color fade. It is an ideal choice for places such as hotel, school, office and factory where background music and paging is needed.

FEATURES

- ⦿ Clear and sonorous sound
- ⦿ Long life
- ⦿ Rated power output at 20W
- ⦿ 6.5" paper cone driver unit
- ⦿ ABS Ivory White engineering plastic
- ⦿ Driver surround excellent damping
- ⦿ Built-in 70V/100V transformer

Specifications	
Model	NVS-10350020CS
Rated Power	20W
Driver Size	6.5" X 1, 1"X 1
Frequency Response	60Hz -18kHz
Power Taping Options	10/20W
Input Voltage/Impedance	70V/100V
Sensitivity(1m,1w)	90dB±2dB
Maximum SPL(1m)	101dB±2dB
Weight	1.8kg
Diamension	Φ228×95mm
Cutout Size	Ø194 - Ø200mm

ORDERING INFORMATION

Part Number	Description	Standard Quantity
NVS-10350020CS	Coaxial Ceiling Speaker 20W	1