

## SAFENOR LED EXIT SIGN



### FEATURES

- Aluminous Frame with clear acrylic panel
- Single-face or Double faces are available.
- Green background and white lettering, others available upon request
- Replaceable PVC pictogram
- Wall mounting and Suspend mounting.
- IP20, RoHS compliant
- Replaceable pictogram insert.
- Ni-cd Battery
- Test switch and power indicator.
- AC/DC Operation 6pcs straw hat LED

### TECHNICAL PARAMETERS

Characteristic	Value
Power Consumption	4W
Product size	355*145*28mm
Panel Thickness	1 mm
Battery	Ni-cd Battery (1.2V 600mah)
Lamps	LED 2.5 W
Duration discharge time	2 ~3 hours
Viewing Distance	30M
Ambient Temperature	-5 C to +45 C
Working Voltage	220V
Charging Time	24 hrs

## ORDERING GUIDE

Model	Pictogram Types	Number of faces	Mounting Type	Housing Colour (XX)
NFE	A: B: C: D: E: F: G: H: J: K: L: M: N:	1. Single 2. Double	00: None RC: Recessed Ceiling SC: Surface Ceiling SW: Surface Wall SE: Surface End	GN: Green BK: Black WH: White

## EXAMPLE

Single Face

**NFE** **G** **1** **00** **GN**

Description: Safenor LED exit Sign Pictogram Type-G Single Face, Green

Double Face

**NFE** **G** **2** **00** **GN**

Description: Safenor LED exit Sign Pictogram Type-G Double Face, Green