

Surface Mount Fireproof Speaker 12W



DESCRIPTION

The NVS-11340012CS is a 12W Surface Mount Fireproof Speaker. It complies with the EN54 Standard and has a 100V transformer. The 6.5" speaker driver is built-in and has a wide frequency response of 200 to 16,000 Hz. The speaker dome is composed of ABS material and the mesh is made of Aluminium. It also includes a thermal fuse and ceramic connector to prevent overheating.

FEATURES

- ⦿ IP rating of IP32
- ⦿ Complied with EN54 Standard
- ⦿ Multiple power taping-12/6/3 W
- ⦿ Thermal Fuse and Ceramic Connector to prevent Overheating
- ⦿ Mesh is made up of Aluminium
- ⦿ Speaker Dome is made up of ABS material

| Specifications | |
|----------------------------|---|
| Model | NVS-11340012CS |
| Driver size | 6.5"x1 |
| Rated Power | 12W |
| Frequency Response (-10dB) | 200Hz-16KHz |
| Sensitivity (1m, 1W) | 91.2dB SPL |
| Maximum SPL (1m) | 102dB |
| Impedance (1KHz) | 833Ω(12W)-1.66KΩ(6W)-3.33KΩ(6W) |
| Coverage Angle (-6dB) | 180° (500 Hz), 95.6° (1 KHz), 116° (2 KHz), 48° (4 KHz) 35° (8 KHz) |
| Directivity Index (dB) | -3.8 (500 Hz), 3.4 (1 KHz), 5.1 (2 KHz), 9.1 (4 KHz) 10.8 (8 KHz) |
| Directivity Factor (Q) | 0.4 (500 Hz), 2.2 (1 KHz), 3.2 (2 KHz), 8.2 (4 KHz) 12 (8 KHz) |
| Dimension | Ø 203x95 mm |
| Weight | 1.02 Kg |

ORDERING INFORMATION

| Part Number | Description | Standard Quantity |
|----------------|-------------------------------------|-------------------|
| NVS-11340012CS | Surface Mount Fireproof Speaker 12W | 01 |