


# 1.00 Sq.mm Multi Conductor Control Cable

 POLYNOR

The Flexible Control Cables from Norden are used in Office Equipment, Electronic Control Systems, Power Stations, Air-Condition Systems, engineering projects for control, vision and measurement purposes. They are very flexible due to the use of thin multicore copper as conductor. They can be used in wet or dry Internal applications but must be used in duct for external application.



UL File No : E318213

## CABLE CONSTRUCTION

### Conductor

Solid Bare Copper (Class 5 according to BS EN 60228:2005)

### Conductor Size

1.00 mm<sup>2</sup>

### Standard Packing Mode

Cutof Length/ Wooden Reel

### Insulation

Flame Retardant PVC

### Sheath

PVC (Polyvinyl Chloride) or LSZH (Low Smoke Zero Halogen)

### Core Identification

Black with white numbers (3 cores and above to includes Green/Yellow)

### Sheath Color

Grey (standard)

## ELECTRICAL CHARACTERISTICS

Max. Resistance of Conductor @ 20°C	Ω/km	19.5
Current Rating @ 30°C	Amp	15

### ▷ Standard Reference

BS6500, VDE 0250

### ▷ Flame Retardant

IEC/EN 60332-1

### ▷ Voltage Rating

300/500 V

### ▷ Operating Temperature Range

-20°C to +70°C

### ▷ Min. Bend Radius

10 x Overall Diameter

# 1.00 Sq.mm Multi Conductor Control Cable



## ORDERING INFORMATION

▷ YY Series: PVC Insulated/PVC Sheathed Control Cable

Part Number	No. of core x Nom. Cross Sectional Area (n x mm <sup>2</sup> )	No. of Strand x Nom. Diameter (n x mm)	Outer Diameter (mm)	Weight (kg/km)
84-10051502X	2 x 1.00	32 x 0.20	5.3	49
84-10051503X	3 x 1.00	32 x 0.20	5.6	60
84-10051507X	7 x 1.00	32 x 0.20	7.5	104
84-10051512X	12 x 1.00	32 x 0.20	9.9	174

X → BK:Black BL:Blue GN:Green GY:Gray RD:Red WH:White TP:Transparent