SURGE PROTECTOR POWER DISTRIBUTION UNIT



NORDEN Power Distribution Units are designed and manufactured for cabinets. The product is equipped with sockets meeting different systems and UK standards. Additional surge protector to protect electrrical devices from voltage Spikes. Products can be produced according to customer special requirement.

COMPLIANCE

EMC & safety:-EN 55022 Class A,EN 55024,EN 61000-3-2,EN 61000-3-3,FCC Part 15 Class A, ICES-003,PSE, Class A,VDE Socket/Outlet Standard: BS1363 Cable plug: BS1363

DESIGN & MATERIALS

Material of Construction	PC/ABS alloy, High Impart FR thermoplastic –UlL94-V0		
Shell Material & Colour	Aluminium, black		
Outlet Qty.	6 way, 12 way		
Power Input Style	Left end single input style		
Bracket Installation Style	Frontal Installation Style		
Control function	Switch		
Lead length	3 m (other cable length available on request)		

ELECTRICAL & ENVIRONMENTAL DATA

Current Rating	13A 250VAC
Maximum load current available in	13A
Input frequency	50 or 60 Hz
Maximum load capacity	4KW
Operating Environment	-5 °C to +45 °C
Operating Relative Humidity	5 - 95 %
Operating Elevation	0-3000 metres
Storage Temperature	-25 °C to +65 °C
Storage Relative Humidity	5 - 95 %
Storage Elevation	0-15000 metres

SURGE PROTECTOR POWER DISTRIBUTION UNIT

ORDERING INFORMATION

Part Number	Description
1421-106E06N002X	6 Way PDU with main switch, 13Amp, 3mtr, Surge protected UK standard
1421-206E06N002X	6 Way PDU with main switch, 16 Amp, 3mtr, Surge protected UK Standard
1421-406E06N002X	6 Way PDU with main switch, 32 Amp, 3mtr, Surge protected UK Standard
1421-412E12N002X	12 Way PDU with main switch, 32 Amp, 3mtr, Surge protected UK Standard

X: BK(Black)

PACKING INFORMATION

Part Number	Packing Qty.	Packing Mode	N.W (kg)	G.W (kg)	Dimension (mm)
6 Way PDU	10 x 1	Carton Box	13.0	14.0	510 x 190 x 310
12 Way PDU	10 x 1	Carton Box	18.6	19.5	990 x 190 x 310