

# SAFENOR LED EXIT SIGN RUNNING MAN ABS HOUSING SINGLE FACE GREEN



## FEATURES

- Fire retardant ABS housing
- Single and Double face universal
- Replaceable pictogram insert
- Wall mounting and Flush mounting
- IP40, RoHs compliant
- Ni-cad and Ni-MH battery optional
- Maintained and non-maintained operation changeable
- High luminance model optional

## TECHNICAL PARAMETERS

Characteristic	Value
Power Consumption	4W
Light Source	Bright SMD 2835, CCT 6000K, CRI>70
Battery	LiFePO4 with 2000 cycles
Emergency duration time	Maintained, emergency time 3 hours
Viewing Distance	30M
Ambient Temperature	-5°C to +45°C
Installation	Wall and flush mounting
Working voltage	220-240VAC 50/60Hz
Charging Time	24hrs
Pictogram	Pantone 336C or Pantone 354U optional
High luminance option	500cd/m <sup>2</sup>

## ORDERING INFORMATION

Part Number	Description
NFE-5009GN	Safenor LED exit Sign Running man ABS Housing Single Face Green

## PACKING INFORMATION

Part Number	Packing Qty.	Packing Mode	Dimension (mm)
NFE-5009GN	10x1	Carton Box	330x193x53.5

